


Team creates 3-D-printed glucose biosensors

December 6 2018, by Siddharth Vodnala



Graphic shows the 3D printed biosensor for glucose sensing, and illustrates the direct-ink-writing of electrode and enzyme ink. Credit: WSU

A 3-D-printed glucose biosensor for use in wearable monitors has been created by Washington State University researchers.

The work could lead to improved [glucose monitors](#) for millions of people who suffer from diabetes.

Led by Arda Gozen and Yuehe Lin, faculty in the School of Mechanical and Materials Engineering, the research has been published in the

journal *Analytica Chimica Acta*.

People with diabetes most commonly monitor their disease with glucose meters that require constant finger pricking. Continuous glucose monitoring systems are an alternative, but they are not cost effective.


Researchers have been working to develop wearable, flexible electronics that can conform to patients' skin and monitor the glucose in body fluids, such as in sweat. To build such sensors, manufacturers have used traditional manufacturing strategies, such as photolithography or screen [printing](#). While these methods work, they have several drawbacks, including requiring the use of harmful chemicals and expensive cleanroom processing. They also create a lot of waste.

Using 3-D printing, the WSU research team developed a glucose monitor with much better stability and sensitivity than those manufactured through traditional methods.

The researchers used a method called direct-ink-writing (DIW), that involves printing "inks" out of nozzles to create intricate and precise designs at tiny scales. The researchers printed out a nanoscale material that is electrically conductive to create flexible electrodes. The WSU team's technique allows a precise application of the material, resulting in a uniform surface and fewer defects, which increases the sensor's sensitivity. The researchers found that their 3-D-printed sensors did better at picking up glucose signals than the traditionally produced electrodes.

Because it uses 3-D printing, their system is also more customizable for the variety of people's biology.

"3-D printing can enable manufacturing of biosensors tailored specifically to individual patients" said Gozen.



Arda Gozen, assistant professor, WSU School of Mechanical and Materials Engineering, in the Manufacturing Processes and Machinery Lab. Credit: WSU

Because the 3-D printing uses only the amount of material needed, there is also less waste in the process than traditional manufacturing methods.

"This can potentially bring down the cost," said Gozen.

For large-scale use, the printed biosensors will need to be integrated with [electronic components](#) on a wearable platform. But, manufacturers could use the same 3-D printer nozzles used for printing the sensors to print electronics and other components of a wearable medical device, helping to consolidate manufacturing processes and reduce costs even more, he

added.

"Our 3-D printed glucose sensor will be used as wearable sensor for replacing painful finger pricking. Since this is a noninvasive, needleless technique for glucose monitoring, it will be easier for children's glucose monitoring," said Lin.

The team is now working to integrate the [sensors](#) into a packaged system that can be used as a wearable device for long-term [glucose](#)-monitoring.

More information: Sepehr Nesaei et al, Micro additive manufacturing of glucose biosensors: A feasibility study, *Analytica Chimica Acta* (2018). [DOI: 10.1016/j.aca.2018.09.012](https://doi.org/10.1016/j.aca.2018.09.012)

Provided by Washington State University

Citation: Team creates 3-D-printed glucose biosensors (2018, December 6) retrieved 17 April 2024 from <https://techxplore.com/news/2018-12-team-d-printed-glucose-biosensors.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.