

# Fibers from old tires can improve fire resistance of concrete

February 20 2019

---



Credit: CC0 Public Domain

A new way of protecting concrete from fire damage using materials recycled from old tyres has been successfully tested by researchers at the University of Sheffield.

The team used fibres extracted from the textile reinforcement commonly embedded into tyres to guarantee their performance. Adding these fibres to the concrete mix was shown to reduce the concrete's tendency to spall—where surface layers of concrete break off—explosively under the intense heat from a fire.

Using man-made polypropylene (PP) fibres to protect [concrete structures](#) from damage or collapse if a fire breaks out is a relatively well-known technique. Many modern structures, including large scale engineering projects such as Crossrail, have used concrete that includes PP fibres for protection against fire spalling.

The Sheffield study is the first to show that these fibres do not have to be made from [raw materials](#), but can instead be reclaimed from used tyres. The results are published in the journal *Fire Technology*.

"We've shown that these recycled fibres do an equivalent job to 'virgin' PP fibres which require lots of energy and resources to produce," explains lead author Dr. Shan-Shan Huang, in the Department of Civil and Structural Engineering at the University of Sheffield.

"Using waste [materials](#) in this way is less expensive, and better for the planet."

The fibres melt under the intense heat from a fire, leaving networks of tiny channels. This means that moisture trapped within the concrete is able to escape, rather than becoming trapped, which causes the concrete to break out explosively.

"Because the fibres are so small, they don't affect the strength or the stiffness of the concrete," says Dr. Huang.

"Their only job is to melt when heat becomes intense. Concrete is a

brittle material, so will break out relatively easily without having these fibres help reducing the pressure within the concrete."

Protecting the concrete from fire spalling means that steel reinforcements running through the concrete are also protected. When the steel reinforcements are exposed to extreme heat they weaken very quickly, meaning a structure is much more likely to collapse. The Liverpool Waterfront Car Park suffered this kind of damage during a fire in 2017, leading to the entire structure eventually having to be demolished.

Collaborating with Twincon, a Sheffield-based company that develops [innovative solutions](#) for the construction industry, the researchers have also developed technologies for reclaiming the fibres from the used tyres.

This involved separating the fibres from the [tyre](#) rubber, untangling the fibres into strands, and then distributing them evenly into the concrete mixture.

The team plan to continue testing the material with different ratios of the fibres to concrete, and also using different types of concrete. They also plan to find out more about how the materials react to [heat](#) at the microstructure level. By scanning the concrete as it is heated, they will be able to see more precisely the structural changes taking place inside the material.

**More information:** Fabio P. Figueiredo et al, Effects of Recycled Steel and Polymer Fibres on Explosive Fire Spalling of Concrete, *Fire Technology* (2019). [DOI: 10.1007/s10694-019-00817-9](https://doi.org/10.1007/s10694-019-00817-9)

Provided by University of Sheffield

Citation: Fibers from old tires can improve fire resistance of concrete (2019, February 20)  
retrieved 4 May 2024 from <https://techxplore.com/news/2019-02-fibers-resistance-concrete.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.