

Third step boosts solar cell performance

July 31 2019



The team uses solution-processing techniques to create organic solar cells. Credit: KAUST

A three-component light-harvesting layer boosts performance in an organic solar cell.

Adding one extra ingredient to the light-capturing layer of an emerging



solar cell technology can significantly improve all aspects of its energyharvesting performance, KAUST researchers have shown.

The team is developing an alternative to silicon solar technology called organic solar cells, which can be formulated into inks for low-cost production. Although organic solar cells do not yet quite match the lightcapturing efficiency of silicon cells, the three-component design brings them a significant step closer.

There have been significant gains in performance of organic solar cells due to a rethink of their formulation. Typically, the <u>cells</u> consist of two light-capturing molecules: one an electron donor and the other an electron acceptor, which help draw apart the electric charges generated when light strikes the material. Early <u>organic solar cells</u> used molecules called fullerenes as the electron acceptor, but these <u>materials</u> had reached a performance plateau.

"The emergence of nonfullerene acceptors opened a new horizon, boosting the certified power conversion efficiency from 10.9 percent to 15.6 percent in just four years," says Xin Song, a <u>graduate student</u> in Derya Baran's research group in the KAUST Solar Center.

A more recent innovation is to add a small amount of a third component—either an additional <u>electron acceptor</u> or an additional electron donor—into the organic light-harvesting mixture. The third component can improve processability and produce a higher-quality, higher-performance light-harvesting layer. Alternatively, it can absorb light energy at wavelengths complementary to the other two components in the mixture.

Now, Baran, Song and their collaborators have identified a third component that simultaneously improves both aspects of device performance. The team incorporated a second <u>electron donor</u> called



BIT-4F-T into an organic solar material. This molecule was selected for several reasons, Song explains: its deep ionization potential, which benefits the cell's electronic properties; its complementary light absorption to harvest more light; and its high crystallinity, which improves processability.

Together, these enhancements boosted the solar cell's performance by 15 percent compared with the two-component mixture, allowing it to reach an overall solar energy <u>power-conversion efficiency</u> of 14 percent. Cells containing BIT-4F-T also retained significantly more performance over time.

The team next plans to investigate whether the three-component material can be produced using a manufacturing-friendly, large-scale coating technology while still maintaining superior device stability, Song says. The researchers will also test the material in a tandem solar cell, coating the ternary organic mixture onto another solar material. "From our simulation, the tandem configuration will push the efficiency over 17 percent," says Song.

More information: Xin Song et al. Dual Sensitizer and Processing-Aid Behavior of Donor Enables Efficient Ternary Organic Solar Cells, *Joule* (2019). DOI: 10.1016/j.joule.2019.01.009

Provided by King Abdullah University of Science and Technology

Citation: Third step boosts solar cell performance (2019, July 31) retrieved 27 July 2024 from <u>https://techxplore.com/news/2019-07-boosts-solar-cell.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is



provided for information purposes only.