

## Photoelectrochemical water-splitting efficiency hits 4.5%

January 16 2020



Credit: Ecole Polytechnique Federale de Lausanne

Solar-to-fuel conversion offers a promising technology to solve energy problems, yet device performance could be limited by undesired sunlight absorption. Researchers show copper thiocyanate can assist hole transport in oxide photoelectrodes and enable a 4.55 percent solar-tohydrogen efficiency in tandem devices.



Photoelectrochemical (PEC) water splitting for hydrogen fuel generation has been considered the Holy Grail of electrochemistry. But to achieve it, many scientists believe the materials have to be abundant and low cost.

The most promising oxide photocathodes are cuprous oxide ( $Cu_2O$ ) photoelectrodes. In 2018 and 2019, researchers at EPFL achieved champion performance with cuprous oxide, rivaling photovoltaic (PV) semiconductor-based photocathodes.

But there was still a piece missing from the puzzle. Even state-of-the-art  $Cu_2O$  photocathodes still use metallic back contacts (copper or gold), allowing for considerable electron-hole recombination. Other disadvantages include high cost and that the metal contact won't allow unabsorbed sunlight to pass through.

Now, scientists at EPFL show for the first time, that copper thiocyanate (CuSCN) can be used as a transparent and effective hole transport layer (HTL) for  $Cu_2O$  photocathodes with overall enhanced performance. The research was led by Professors Anders Hagfeldt, Michael Grätzel, and Kevin Sivula at EPFL's Institute of Chemical Sciences and Engineering.

Detailed analysis on two types of CuSCN showed that a defective structure could be beneficial for hole conduction. Moreover, due to the coincidental alignment between valence bands of CuSCN and  $Cu_2O$ , the band-tail states assisted hole transport in CuSCN was discovered to allow smooth hole conduction while efficiently block electron transport.

The optical advantages of CuSCN were further exhibited through a standalone PEC-PV tandem delivering a solar-to-hydrogen efficiency of 4.55 percent. This efficiency (4.55 percent for 12 h) is currently the highest among all  $Cu_2O$ -based dual-absorber tandems.



The study presents a clear and impressive advancement beyond the stateof-the-art  $Cu_2O$  photocathodes, which can contribute and inspire future development in the field.

"Though top numbers are achieved with the <u>oxide</u> material in this work, we believe higher values are not far," says Pan Lingfeng, the paper's first author. "At least three aspects are found to be not optimal, but improving them is very feasible. The efficiency value is getting closer and closer to the one that was previously thought to be the threshold for commercialization."

**More information:** Linfeng Pan et al. Cu<sub>2</sub>O photocathodes with bandtail states assisted hole transport for standalone solar water splitting, *Nature Communications* (2020). DOI: 10.1038/s41467-019-13987-5

Provided by Ecole Polytechnique Federale de Lausanne

Citation: Photoelectrochemical water-splitting efficiency hits 4.5% (2020, January 16) retrieved 27 April 2024 from https://techxplore.com/news/2020-01-photoelectrochemical-water-splitting-efficiency.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.