

# Technique harvests waste heat from untapped sources

April 15 2020, by Anne M Stark

---



Credit: CC0 Public Domain

Thermoelectric materials convert heat to electricity or vice versa. However, their application to harvest waste heat is limited by challenges in fabrication and materials. Finding cost-effective ways to cover large

and potentially complex surfaces has remained an issue but is crucial to take advantage of waste heat sources.

Lawrence Livermore National Laboratory (LLNL) material scientists have used an additive manufacturing technique, called cold-spray deposition, to create [thermoelectric generators](#) that can harvest waste heat from previously inaccessible sources, such as pipes with complex geometries. The generators display good performance over a wide temperature range.

Waste heat is a huge untapped resource. Thirteen quadrillion BTUs of energy is lost annually through waste heat by U.S. industry. A BTU, or British Thermal Unit, is a unit of measurement for energy; 3,600 BTU is equivalent to about 1 kilowatt-hour.

But only three quads of BTU are recovered and put to work through co-location of processes, energy recovery through boilers and thermoelectric recovery. One challenge in harvesting the energy is devising a generator that can efficiently harvest the [heat](#). For a thermoelectric material to be effective it must convert temperature gradient into voltage. It also requires high electrical conductivity, but low thermal conductivity.

In the new research, appearing in the *Journal of The Minerals, Metals & Materials Society (JOM)*, the team cold-sprayed a bismuth-telluride powder on substrates ranging from stainless steel to aluminum silicate and quartz. The sprayed material had a randomly oriented microstructure largely free from pores and the cold-spray deposition was achieved without substantial compositional changes.

"These results demonstrate the power and versatility of cold-spray additive manufacturing and provide a pathway toward fabrication of thermoelectric generators in complex geometries that are inaccessible to

generators made by traditional approaches," said LLNL materials physicist Alex Baker, lead author of the paper.

Cold-spray deposition of coatings is widely used across industry for corrosion-resistant claddings, surface functionalization and localized repair. In this technique, micron-scale metal particles are entrained in supersonic gas and directed onto a metal surface. Upon impact, the particles plastically deform and bond with the surface or one another.

Cold-spray has typically been limited to malleable materials, making it well suited for [structural elements](#) and alloys, but is not well equipped for functional materials, which are typically brittle. In collaboration with industrial partner TTEC Thermoelectric Technologies, LLNL is working to extend the range of materials that can be cold-sprayed as part of the Technology Commercialization Funds (TCF) program funded by the Department of Energy.

"Cold-spray operates at comparatively low temperatures, beneath the melting point of most functional materials, so it is attractive to consider the possibility of an additive manufacturing technique that preserves the tailored microstructure that drives functional properties," Baker said.

Thermoelectric generators (TEGs) have no moving parts, are not based on [chemical reactions](#) and have long operating life with no maintenance requirements, making them excellent candidates for power sources on remote or inaccessible locations. To date, adoption of TEGs to harvest [waste heat](#) has been limited, in part due to the difficulty of fabricating parts that make intimate thermal contact with cooling fins or radiated from transfer pipes.

The team concluded that cold-spray deposition can fabricate bulk pieces of thermoelectric bismuth-telluride on a wide variety of substrates, without loss of structural integrity, demonstrating that cold-spray is a

viable alternative to traditional manufacturing approaches for thermoelectric materials.

"One of our goals is to bring this technology to LLNL, where it can be applied to a broad range of additive manufacturing issues," said Harry Radousky, TCF principal investigator.

**More information:** Alexander A. Baker et al. Cold Spray Deposition of Thermoelectric Materials, *JOM* (2020). [DOI: 10.1007/s11837-020-04151-2](https://doi.org/10.1007/s11837-020-04151-2)

Provided by Lawrence Livermore National Laboratory

Citation: Technique harvests waste heat from untapped sources (2020, April 15) retrieved 28 April 2024 from <https://techxplore.com/news/2020-04-technique-harvests-untapped-sources.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.
---