

Experimental, simulation results reveal how coaxial, co-rotating helicopter rotors may lead to a quieter hover

December 1 2020, by U.s. Army Devcom Army Research Laboratory Public Affairs



The U.S. Army looks to silent technology solutions to quiet rotors. Credit: U.S. Army



Imagine a silent helicopter stealthily moving troops and supplies around a future battlefield. U.S. Army researchers look to helicopter noise reduction technology as a top priority in aircraft design.

At the U.S. Army Combat Capabilities Development Command, now known as DEVCOM, Army Research Laboratory, researchers collaborated with Uber and the University of Texas at Austin to investigate the acoustic properties of electric vertical takeoff and landing aircraft, which use distributed electric propulsion to power flight.

These eVTOL vehicles may aid the Army with important tasks such as aerial surveillance and cargo transport; however, they feature smaller rotors than traditional helicopters. As a result, eVTOL rotors may emit a different sound signature that researchers will have to take into consideration.

"The <u>noise</u> you hear from these smaller rotors is generated through fundamentally different physical mechanisms," said Dr. George Jacobellis, Army research engineer at the laboratory's Vehicle Technology Directorate. "Traditional modeling techniques need to be improved to account for all of the noise generated so that vehicle designers can be aware of what will actually be heard."

Standard helicopter noise simulations focus primarily on predicting thickness noise and loading noise, because they constitute the dominant noise sources for large helicopters.

Thickness noise stems from the displacement of the air by the <u>rotor</u> <u>blades</u>, while loading noise occurs when lift and drag forces act on the air that flows around the rotary wings. Together, they make up what experts refer to as tonal noise.

In contrast, Army researchers suspected that eVTOL rotors generate



more broadband noise, which refers to sounds caused by turbulence, than tonal noise.

"We didn't know whether broadband noise was important or not, but we knew that the tonal and broadband noise scaled differently," Jacobellis said. "We thought that as rotors became smaller there would be some point at which broadband noise would be the dominant source."

The team confirmed their hypothesis in their research study, which not only measured the acoustic characteristics of various eVTOL <u>rotor</u> configurations but also assessed the modeling capabilities of helicopter noise simulations for eVTOL rotors.



The test stand used during the experiment had the rotor shaft oriented horizontally to allow researchers to make acoustic measurements. Credit: U.S.



Army

During the field experiment, the researchers set up a test stand with two electrically-powered rotors and recorded the noise generated above and below the rotor plane with nine microphones placed in a circular array surrounding the rotor hub.

For the simulations, the team utilized the Rotorcraft Comprehensive Analysis System coupled with a separate program called PSU-WOPWOP, a routine noise prediction code named after an onomatopoeia for the sound that helicopter blades make.

"RCAS computes the aerodynamic loads, or forces, on the blades as well as the bending and twisting of the blades," Jacobellis said. "This information is necessary to use as inputs to PSU-WOPWOP, which computes the noise generated by the rotor. Connecting the two programs required a significant amount of work, which was done by our group as well."

The researchers modeled the broadband noise in PSU-WOPWOP with Pegg's method, one of the two settings present in the simulation program with the other called Brooks' method.

While Pegg's method makes broadband noise predictions based off of experimental data of the entire rotor, Brooks' method accounts for the unique distribution of lift along the blade.

"[These technologies] are promising in their ability to predict the noise of eVTOL rotors, but we need to do more work to obtain acceptable accuracy," Jacobellis said. "The next steps are to implement the Brooks method for higher accuracy acoustic predictions and to compare the



unsteady loads between the simulation and experiment to check the accuracy of the simulations in predicting the unsteady loads. The Brooks method should be better at capturing unique configurations and loading distributions."

Researchers also found that co-axial co-rotating rotors, or stacked rotors, may potentially offer better performance and lower noise than a conventional rotor. Unlike conventional rotors which employ blades arranged in a single plane, stacked rotors place blades in multiple planes.

According to the results of their study, stacked rotors with equally spaced rotor blades produced the lowest noise level, around the same level as that of a traditional rotor.

By investigating different values of axial spacing, Army researchers believe that they may uncover a stacked rotor configuration that produces lower noise than the conventional rotor.

"I do think that a stacked rotor can be beneficial for eVTOL applications," Jacobellis said. "The added degree of freedom for the design will allow for gains in efficiency and control over the acoustic signature, which has been shown in the results. More investigation is needed, however, to quantify the noise reduction with axial spacing."

Provided by The Army Research Laboratory

Citation: Experimental, simulation results reveal how coaxial, co-rotating helicopter rotors may lead to a quieter hover (2020, December 1) retrieved 3 May 2024 from <u>https://techxplore.com/news/2020-12-experimental-simulation-results-reveal-coaxial.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.