

# How short circuits in lithium metal batteries can be prevented

January 19 2021



There are high hopes for the next generation of high energy-density lithium metal batteries, but before they can be used in our vehicles, there are crucial problems to solve. An international research team led by Chalmers University of Technology, Sweden, has now developed concrete guidelines for how the batteries should be charged and operated, maximising efficiency while minimising the risk of short circuits. Credit: Chalmers University of Technology

There are high hopes for the next generation of high energy-density lithium metal batteries, but before they can be used in our vehicles, there are crucial problems to solve. An international research team led by Chalmers University of Technology, Sweden, has now developed

concrete guidelines for how the batteries should be charged and operated, maximizing efficiency while minimizing the risk of short circuits.

Lithium metal batteries are one of several promising concepts that could eventually replace the lithium-ion batteries which are currently widely used—particularly in various types of electric vehicles.

The big advantage of this new battery type is that the energy density can be significantly higher. This is because one electrode of a battery cell—the anode—consists of a thin foil of lithium metal instead of graphite, as is the case in [lithium-ion batteries](#). Without graphite, the proportion of active material in the battery cell is much higher, increasing energy density and reducing weight. Using lithium metal as the anode also makes it possible to use high-capacity materials at the other electrode—the cathode. This can result in cells with three to five times the current level of [energy density](#).

The big problem, however, is safety. In two recently published [scientific articles](#) in the prestigious journals *Advanced Energy Materials* and *Advanced Science*, researchers from Chalmers University of Technology, together with colleagues in Russia, China and Korea, present a method for using the lithium metal in an optimal and safe way. It results from designing the battery in such a way that, during the [charging process](#), the metal does not develop the sharp, needle-like structures known as dendrites, which can cause short circuits, and, in the worst cases, lead to the battery catching fire. Safety during charging and discharging is the key factor.

"Short circuiting in [lithium metal batteries](#) usually occurs due to the metal depositing unevenly during the charging cycle and the formation of dendrites on the anode. These protruding needles cause the anode and the cathode to come into direct contact with one another, so preventing

their formation is therefore crucial. Our guidance can now contribute to this," says researcher Shizhao Xiong at the Department of Physics at Chalmers.

## Optimized charging provides safer batteries

There are a number of factors that control how the lithium is distributed on the anode. In the electrochemical process that occurs during charging, the structure of the lithium metal is mainly affected by the current density, temperature and concentration of ions in the electrolyte.

The researchers used simulations and experiments to determine how the charge can be optimized based on these parameters. The purpose is to create a dense, ideal structure on the lithium metal [anode](#).

"Getting the ions in the electrolyte to arrange themselves exactly right when they become lithium atoms during charging is a difficult challenge. Our new knowledge about how to control the process under different conditions can contribute to safer and more efficient [lithium metal](#) batteries," says Professor Aleksandar Matic from Chalmers' Department of Physics.

**More information:** Yangyang Liu et al. Insight into the Critical Role of Exchange Current Density on Electrodeposition Behavior of Lithium Metal, *Advanced Science* (2021). [DOI: 10.1002/advs.202003301](https://doi.org/10.1002/advs.202003301)

Xieyu Xu et al. Role of Li-Ion Depletion on Electrode Surface: Underlying Mechanism for Electrodeposition Behavior of Lithium Metal Anode, *Advanced Energy Materials* (2020). [DOI: 10.1002/aenm.202002390](https://doi.org/10.1002/aenm.202002390)

Provided by Chalmers University of Technology

Citation: How short circuits in lithium metal batteries can be prevented (2021, January 19)  
retrieved 30 May 2023 from <https://techxplore.com/news/2021-01-short-circuits-lithium-metal-batteries.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.