

Mixing it up: A low-cost way to make efficient, stable perovskite solar cells at commercial scale

June 30 2021



An image of solar cells on a rooftop at Monash University's Clayton campus in Melbourne, Victoria. Credit: Monika Michalska (Exciton Science)

A key component of next-generation solar panels can be created without

expensive, high-temperature fabrication methods, demonstrating a pathway to large scale, low-cost manufacturing for commercial applications.

Nickel oxide (NiO) is used as an inexpensive hole-transport layer in [perovskite solar cells](#) because of its favorable optical properties and long-term stability.

Making high-quality NiO films for [solar cells](#) usually requires an energy intensive and high-temperature treatment process called thermal annealing, which is not only costly, but also incompatible with plastic substrates, until now precluding the use of NiO in the proposed manufacture of printed photovoltaics at commercial scale.

However, researchers at the ARC Centre of Excellence in Exciton Science, based at Monash University, have identified a way to create NiO films of sufficient quality in solution and at relatively low temperatures of less than 150 degrees Celsius.

The researchers, in collaboration with their colleagues at CSIRO, Australia's national science agency, used 4-hydroxybenzoic acid (HBA) or trimethyloxonium tetrafluoroborate (Me_3OBF_4) ligand-modified NiO nanoparticles and a microfluidic mixer, which promotes high-pressure mixing of low volume liquids, to distribute the nanoparticles evenly prior to depositing them on the substrate.

The [chemical process](#), developed in collaboration with the Australian National Fabrication Facility, could contribute to the scalable fabrication of inorganic and inexpensive, high-performance films able to be used in the commercial production of flexible solar panels.

The researchers have recorded power-conversion efficiencies of 17.9% and 17.5% respectively in prototype devices, compared to 16% for a

previous comparable approach, which lacked the advantages of the ligand exchange and also required a post-processing oxygen-plasma treatment step.

Significantly, the new devices exhibited just a 0.2% reduction in efficiency over an intensive 300-hour testing period, providing a strong indication of their potential suitability for [commercial applications](#).

Joint lead author Monika Michalska of Monash University said: "Our work showcases that high-temperature processing of functional materials for solar cells can be omitted using facile processing ways. It is a crucial step for commercialization of perovskite technology."

The results have been published in the journal *Solar RRL*.

More information: Monika Michalska et al, Microfluidic Processing of Ligand-Engineered NiO Nanoparticles for Low-Temperature Hole-Transporting Layers in Perovskite Solar Cells, *Solar RRL* (2021). [DOI: 10.1002/solr.202100342](https://doi.org/10.1002/solr.202100342)

Provided by ARC Centre of Excellence in Exciton Science

Citation: Mixing it up: A low-cost way to make efficient, stable perovskite solar cells at commercial scale (2021, June 30) retrieved 18 April 2024 from <https://techxplore.com/news/2021-06-low-cost-efficient-stable-perovskite-solar.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.