


Smart fabrics and self-powered sensing

June 15 2021, by Thamarasee Jeewandara



Preparation of LM sheath-core microfibers. (A) Schematic setup and the main components for the coaxial wet-spinning process for producing LM sheath-core microfibers. (B) A single as-spun fiber with the length of 380 m was collected on a continuously winding collector. (C) Microscopic images of LM sheath-core microfiber and human hair. (D) Photo of the microfiber threaded into a needle. (E) SEM image of the external surface of the microfiber. (F) SEM image of a


knotted microfiber. (G) An LED can be lit up through a 55-cm-long activated LM sheath-core microfiber at a voltage of 3 V. (H) The cross-sectional SEM and corresponding elemental mapping images of the microfiber. Photo credit: Lijing Zheng, Donghua University. Credit: Science Advances, doi: 10.1126/sciadv.abg4041

Smart fabrics and [wearable electronics](#) can be developed using highly conductive and stretchy fibers. Most of these fiber conductors are, however, strain sensitive with limited conductance on stretching. As a result, a new strategy can be introduced by rearranging the geometry of the conductive path for stable conductance. In a new report now published on *Science Advances*, Lijing Zheng and colleagues in China and Germany, described a [coaxial wet-spinning process](#) to continuously develop intrinsically stretchable and highly conductive, yet conductance-stable liquid metal (LM) sheath-core microfibers. The team stretched the microfibres up to 1170 percent and fully activated the conductive path to obtain a very high conductivity of 4.35×10^4 S/m and a resistance change of only 4 percent at 200 percent strain. The microfiber could be woven easily into everyday glove fabrics and as excellent joule heaters, electro-thermochromic displays and self-powered wearable sensors.

Stretchable fiber conductors

Stretchable fiber conductors can be easily developed into fabrics with high air permeability and can be well integrated as wearable sensors with [increasing interest](#). Stretchable conductive fibers have highly sensitive [conductance](#) changes and promote stable conductance. Recent developments in high-performance electronics have a high demand for stretchable fiber electrodes or interconnects to steadily transport [electrical signals](#) between active electronic components [without notable conductance loss](#). To overcome existing limits, Zheng et al. embedded

deformable conductive fillers with strain-enhanced conductivity into an elastic matrix to produce ultralong, intrinsically stretchable fiber conductors with stable and high conductance. The research team proposed a coaxial wet-spacing method to prepare super-elastic liquid metal sheath-core microfibers with high and ultra-stable conductance. They then explored the promising applications of the liquid metal sheath-core microfibers in [smart fabrics](#) and self-powered sensing processes, relative to joule heating, [electrothermochromism](#) and [triboelectric](#) properties.




Mechanical properties and strain-insensitive conductance of LM sheath-core microfibers. (A) Tensile stress-strain curves of LM sheath-core microfibers and the hysteresis loops measured at increasing strains (stretching rate: 20 mm/min).

(B) Cyclic loading-unloading curves at a fixed strain of 100% for 100 cycles (stretching rate: 20 mm/min; waiting time: 10 min). (C) Resistance changes of the stretch-induced conductivity activation of microfiber after freezing treatment. (D) Strain-dependent resistance changing rate of LM sheath-core microfibers with six different fluoroelastomer loadings [CPVDF-HFP-TFE = 0 (pure LM), 3, 5, 7, 9, and 11 wt %]. (E) Histogram of resistance change rates at fixed strains of different microfibers. (F) Comparison of the maximum strain, initial conductivity, and resistance change rate at 200% strain of LM sheath-core microfiber with other reported strain-insensitive and LM-based stretchable fiber conductors. (G) Resistance changes of the LM sheath-core microfiber over 600 cycles between 0 and 100% strain. (H to J) Resistance changes of the microfiber upon pressing, twisting, and bending. Credit: Science Advances, doi: 10.1126/sciadv.abg4041

The experiments—preparing the liquid-metal (LM) sheath-core microfibers.

Zheng et al. used coaxial wet-spinning to prepare liquid metal sheath-core microfibres and improved the fiber quality by smoothly solidifying the spinning solution. They used three spinning solutions in the inner channel and distilled water in the outer channel as the coagulating bath. The team also introduced a covalent network in the sheath post-ultraviolet polymerization to improve the toughness and elastic recovery of the LM sheath-core fiber. Based on the strategy, Zheng et al. could continuously wet-spin the LM sheath-core microfibers into an ideally unlimited length. After fully drying the [microfiber](#), they imaged the product [using scanning electron microscopy](#) (SEM) to observe a uniform and regular surface. The team next sowed good electrical conductivity of the fibers using a light-emitting diode (LED).



Mechanism of the strain-insensitive conductance of LM sheath-core microfibers. (A) Photographs of EGaIn droplet surface reconciliation on PVDF-HFP-TFE film during stretching and releasing. (B) Schematic illustration of the surface creation and readjustment of EGaIn on the PVDF-HFP-TFE film through the dipole-dipole interactions between Ga₂O₃ layer and polar C-F groups. (C) Ga 3d XPS spectrum of LM particles. a.u., arbitrary units. (D) Attenuated total reflection–Fourier transform infrared (ATR-FTIR) spectra of PVDF-HFP-TFE and PVDF-HFP-TFE/LM composite (CPVDF-HFP-TFE = 7 wt %) in the C-F stretching region. (E) Polarizing micrographs of the LM sheath-core microfiber during stretching observed in the reflection mode. (F) 2D SAXS patterns and scattering intensity plots against q (the integration area is the selected rectangular area) of the microfiber at strains of 0 and 300%, respectively. (G) SAXS azimuth integration and corresponding Lorentz fitting curve. The inset picture is the 2D image of the fiber at 300% strain. Photo credit: Lijing Zheng, Donghua University. Credit: Science Advances, doi: 10.1126/sciadv.abg4041


Mechanical properties and strain-insensitive conductance

To understand the highly elastic stretchability and cyclability of LM sheath-core microfibers, the scientists next conducted cycling tensile tests to note good elastic recovery of 100 percent after 100 cycles. To impart electric conductivity on the LM sheath-core microfiber, Zheng et al. next used a sequential freezing-plus-stretching strategy for conductivity activation. The resulting excellent strain-insensitive conductance of the microfiber contributed to further studies on the stability and durability of electrical properties in real-time, for practical applications within smart fabrics and wearable electronics. To fully sinter the [liquid-metal particles](#) for activated conductivity, the scientists used a sequential 'freezing-plus-stretching' strategy. Due to its abnormal volume expansion behavior, the LM expanded instead of shrinking at low temperatures. As a result, the liquid nitrogen freezing-induced phase and stiffness change assisted the LM particles to pierce through the oxide and elastomer coating for partial activation of the conductive path. Subsequent mechanical stretching of the material to 200 percent reduced the resistance to allow a considerably high conductivity. Repeated stretching and recovery showed a small amplitude of resistance changes for the successful construction of stable and continuous conductive networks. Based on the excellent strain-insensitive conductance of the microfiber, Zheng et al. studied the stability and durability of the electrical properties in real-time applications. The results highlighted the high and strain-insensitive conductance of LM sheath-core microfibers that were not largely affected by deformation, with practical applications in smart fabrics and wearable electronics.

Mechanisms of strain-insensitive conductance

To understand the mechanism of excellent conductance within the LM sheath-core microfiber, Zheng et al. next investigated the interaction between the fluoroelastomer and the liquid-metal boundary. The liquid


metal maintained very high surface tension and underwent fully recoverable shape deformation to suggest that LM could reconcile its surface to [form a firm interface with the fluoroelastomer](#) during strain-insensitive conductance. The team supported the presence of the surface oxidation layer on the LM particles using a 3D [X-ray photoelectron spectroscopy](#) (XPS) spectrum. The results showed the important role of the dipolar attraction between the LM oxidation layer and fluoroelastomer during LM deformation and high conductance tolerance. The team then used the [small-angle X-ray scattering](#) method to further investigate the small microstructural changes of the fiber.



Joule heating properties of LM sheath-core microfibers. (A) The stepwise temperature changing curve and corresponding infrared thermal images of the LM sheath-core microfiber with the applied voltage from 0 to 1.2 V. (B) Cyclic stability test of the joule heating performance of the microfiber by switching voltage between 0 and 0.8 V. (C) The enlarged image of the dashed area in (B) shows the temperature changes in one on-off cycle. (D) Infrared thermal images of the fiber embedded in an elastic fabric glove (applied voltage, 0.4 V) as the fingers bend. (E) Microscopic images of the electrothermochromic microfibers and photographs of the fibers embedded in a fabric by switching the voltage on and off. Photo credit: Lijing Zheng, Donghua University. Credit: Science

Joule heating effect

The scientists next studied the potential applications of integrating the LM sheath core microfibers in smart fabrics. Due to the fine nature of the fiber with a small [Young's modulus](#), it wasn't feasible to integrate the fiber with fabrics, since it could not influence the mechanical properties of the fabric. The fiber could, however, be used as an electrical heater via the joule heating effect due to its strain-insensitive conductance. For instance, the temperature of the fiber increased uniformly and simultaneously with an applied DC voltage. The team also embedded the LM sheath-core microfiber into an elastic spandex glove and demonstrated multiple findings with smart fabrics to prove the microfiber's potential during intelligent display and adaptive camouflage. The LM sheath-core microfibers also acted as ideal, highly stretchable self-powered sensors based on the single-electrode-mode triboelectric mechanism. The ultrasoft Young's modulus and ultrahigh stretchability of the LM sheath-core microfibers made them suitable for imperceptible wearable sensing. The team repeatedly contacted the LM sheath-core microfiber with diverse materials including cotton, silk and aluminum foil to monitor the induced voltage and current. During [skin contact](#) on the human wrist, the fiber demonstrated powerful sensing potential as a self-powered wearable sensor.



Application of the LM sheath-core microfibers/fabrics in self-powered sensors. (A) Working mechanism of LM sheath-core microfiber-based self-powered sensor. (B) Comparison of the Young's moduli and relative triboelectric polarities of common triboelectric materials. (C) Voltage signals generated by contacting LM microfiber with five different triboelectric materials at the motion frequency of 2 Hz. The length of the fiber is 4 cm. (D) Voltage signals under different frequencies generated by contacting the fiber with silk. (E) Voltage signals under different strain levels of the fiber at the motion frequency of 2 Hz. The length of the fiber is 1 cm. (F) Photos and corresponding voltage signals by bending the fiber sensor–embedded spandex glove worn on a prosthetic hand. (G) Photos and corresponding voltage signals of the fiber sensor adhered to a human wrist. Photo credit: Lijing Zheng, Donghua University. Credit: Science Advances, doi: 10.1126/sciadv.abg4041

Outlook

In this way, Lijing Zheng and colleagues used coaxial wet-spinning based on liquid metal particles and polymer materials to develop a highly conductive, intrinsically stretchable LM sheath-core microfibers with high stretchability and strain-insensitive conductance. The team noted applications of the microfibers during joule heating, electrothermochromism and self-powered sensing for potential applications with smart textiles and wearable sensors.

More information: 1. Zheng L. et al. Conductance-stable liquid metal sheath-core microfibers for stretchy smart fabrics and self-powered sensing, *Science Advances*, [DOI: 10.1126/sciadv.abg4041](https://doi.org/10.1126/sciadv.abg4041)

2. Tan J. Y. et al. A transparent, self-healing and high- κ dielectric for low-field-emission stretchable optoelectronics, *Nature Materials*, 10.1038/s41563-019-0548-4

3. Liu Z. F. et al. Hierarchically buckled sheath-core fibers for superelastic electronics, sensors, and muscles, *Science*, 10.1126/science.aaa7952

© 2021 Science X Network

Citation: Smart fabrics and self-powered sensing (2021, June 15) retrieved 13 March 2024 from <https://techxplore.com/news/2021-06-smart-fabrics-self-powered.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.
