Novel method to fabricate lead halide perovskite solar cells with record efficiency



Fig. 1. Chemical structure of PEAI cations and schematics of the fabrication procedure and device architecture used in this work.(A) Chemical structure of PEAI, Cl-PEAI, and F-PEAI. (B) Schematic presentation of the fabrication procedure of the perovskite active layer. (C) Solar cell device structures with the different combinations of passivated interfaces. Credit: DOI: 10.1126/sciadv.abj7930



In a joint effort between Pavia University (Italy) and the Center for Advancing Electronics Dresden at Technische Universität Dresden (Germany), researchers developed a novel method to fabricate lead halide perovskite solar cells with record efficiency. Results have been published in *Science Advances*.

Metal halide perovskites have been under intense investigation over the last decade due to the remarkable rise in their performance in <u>optoelectronic devices</u> such as solar cells or light-emitting diodes. The most efficient devices, fabricated in the so-called 'standard architecture' commonly include processing steps performed at high temperature, thus increasing their energy payback time and limiting the possibility to integrate them in emerging applications such as flexible and wearable electronics. An alternative device architecture—termed the 'inverted architecture'—eliminates the need for high temperature processing, but generally leads to a lower photovoltaic efficiency.

The method is based on a modification of the interfaces of the <u>perovskite</u> active layer by introducing small amounts of organic halide salts at both the bottom and the top of the perovskite layer. Such organic halide salts, typically used for the formation of two-dimensional perovskites, led to the suppression of microstructural flaws and passivation of the defects of the perovskite layer. Using this approach, the team has achieved a <u>power conversion efficiency</u> of 23.7%—the highest reported to date for an inverted architecture perovskite solar cell.

"Importantly, the improvement in performance is accompanied by an increase in device stability," says Prof. Giulia Grancini, an associate professor of chemistry at the University of Pavia. Considering that stability remains one of the key hurdles for the commercialization of perovskite solar cells, the simultaneous improvement of efficiency and



stability is particularly promising.

"The fact that our devices are fabricated at low temperatures of less than 100° C and that our approach is fully applicable to the fabrication of large area devices takes us one step closer to large-scale utilization of perovskite solar cells" adds Prof. Yana Vaynzof, Chair for Emerging Electronic Technologies at the Institute for Applied Physics and Photonic Materials and the Center for Advancing Electronics Dresden (cfaed).

The record efficiency achieved by the researchers brings perovskite <u>solar cells</u> to new frontiers. Considering the enhanced stability and the scalability of the novel approach, it's only a matter of time until <u>perovskite solar cells</u> can be found on every rooftop.

More information: Matteo Degani et al, 23.7% Efficient inverted perovskite solar cells by dual interfacial modification, *Science Advances* (2021). DOI: 10.1126/sciadv.abj7930

Provided by Dresden University of Technology

Citation: Novel method to fabricate lead halide perovskite solar cells with record efficiency (2021, December 3) retrieved 4 May 2024 from <u>https://techxplore.com/news/2021-12-method-fabricate-halide-perovskite-solar.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.