

Battery research tackles new challenges for behind-the-meter stationary storage systems

March 25 2022, by Rebecca Martineau



Stationary batteries, like the one pictured, allow buildings to reduce reliance on grid power by storing energy that can be used during times of peak demand.
Credit: Dennis Schroeder, NREL

The national transition to net-zero carbon emissions by 2050 will demand more from our electric grid than ever before. Stationary energy

storage systems are critical to grid resiliency by ensuring that the power from renewable energy sources is available when and where it is needed.

Energy efficient buildings of the future are turning to holistic behind-the-meter storage (BTMS) system designs to minimize costs and grid impacts due to their ability to integrate electric vehicle charging, photovoltaic generation, and building demands using controllable loads to generate and store energy on-site.

As part of the U.S. Department of Energy's BTMS Consortium, researchers at the National Renewable Energy Laboratory (NREL) are leading the development of new lithium-ion (Li-ion) battery designs specific to the stationary storage requirements.

"We already know a lot about Lithium-ion batteries, but batteries for different applications have different requirements," said NREL Researcher and Project Leader Yeyoung Ha. "Our research looks at how to leverage the developments from electric vehicle battery research for new applications in stationary storage."

BTMS systems have different charging and discharging patterns than a typical electric vehicle and require Li-ion battery materials that meet these unique priorities. Li-ion battery designs using a $\text{Li}_4\text{Ti}_5\text{O}_{12}$ (LTO) anode and LiMn_2O_4 (LMO) cathode are promising critical-material-free candidates that offer the safety and long lifespan required of BTMS systems. While these cells in conventional design have a comparatively low energy density, new research at NREL, published in the *Journal of the Electrochemical Society*, delved further into promising opportunities, as well as limitations, of using LTO/LMO battery cells for stationary storage use.

This project evaluated the temperature-dependent performance of LTO/LMO cells with various electrode loadings. Researchers

determined that using thicker electrodes in battery designs can increase the cell capacity and energy density, while decreasing overall cell costs. However, these thicker electrodes require ions to travel a longer path, limiting the utilization of electrodes. Temperature adjustments can alleviate these negative impacts but may introduce added complications. The trick is to design a battery that offers the best balance for stationary applications.

"Our goal with this research is to identify a '[sweet spot](#)' to leverage the advantages of electrode loading and increased temperatures to maximize the performance of LTO/LMO battery cells," Ha said. "Our research refined material designs for BTMS specifically, converting this well-known power chemistry to energy cells."

The NREL team further verified their findings by applying electrochemical modeling to simulate reactions at different temperatures and electrode thickness. This modeling, in alignment with experimental results, emphasized the impact of transport limitations and informed strategies to improve the cell performance. By allowing batteries to have intermittent rest during discharge, instead of being fully discharged as for electric vehicles, the [electrode](#) utilization was significantly improved. Researchers found this type of pulsed discharge is well suited for BTMS stationary applications, where the batteries will be used only when there is intermittent demand and then transitioned back to a resting stage.

Although these optimized LTO/LMO battery cells offer many advantages, the research team is also exploring cathode options that may better meet BTMS system needs. NREL's expertise in materials development will be combined with the cutting-edge electrochemical modeling used in this project to streamline further research into new materials and experimental [battery](#) designs for stationary storage and beyond.

More information: Yeyoung Ha et al, Impact of Electrode Thickness and Temperature on the Rate Capability of $\text{Li}_4\text{Ti}_5\text{O}_{12}/\text{LiMn}_2\text{O}_4$ Cells, *Journal of The Electrochemical Society* (2021). [DOI: 10.1149/1945-7111/ac3781](https://doi.org/10.1149/1945-7111/ac3781)

Provided by National Renewable Energy Laboratory

Citation: Battery research tackles new challenges for behind-the-meter stationary storage systems (2022, March 25) retrieved 10 April 2024 from <https://techxplore.com/news/2022-03-battery-tackles-behind-the-meter-stationary-storage.html>

<p>This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.</p>
--