

Proposed method for wind turbine blade recycling

March 15 2022



Credit: Unsplash/CC0 Public Domain

A group of researchers from Kaunas University of Technology (KTU)

and the Lithuanian Energy Institute proposed a method for wind turbine blade recycling. Using pyrolysis, they broke the composite materials into their constituent parts—phenol and fiber. According to scientists, the extracted materials can be reused, and the process is virtually waste-free.

Wind turbine blades made from glass fiber-reinforced polymer (GFRP) laminate composites can serve for up to 25 years. After that they end up in landfills—GFRP is recognized as hard-to-break-down. This has become a real challenge for the renewable energy industry.

It is estimated that wind turbine blades account for 10 percent of Europe's fiber-reinforced composite material waste. Researchers claim that by 2050, wind turbine blade waste will increase to around two million tons globally. With many countries banning [composite materials](#) from their landfills, recycling the used wind turbine blades becomes a challenge that researchers around the world are trying to solve.

"The aim of cutting [global greenhouse gas emissions](#) to close to zero by 2050 has been voiced several years ago. Since then, more and more countries have been committing to the net-zero goal by investing in renewable energy resources, including wind energy. However, the recycling of the wind turbine blades, which are as long as a football field, very sturdy and include plastic, is the main problem. Without a feasible solution to it, we cannot say that wind energy is fully sustainable and environmentally friendly," says Dr. Samy Yousef, a researcher at Kaunas University of Technology (KTU), Faculty of Mechanical Engineering and Design.

Aiming to tackle this challenge, the research group headed by Dr. Yousef have made several experiments involving decomposing GFRP into its constituent parts.

Waste-free conversion

Due to its strength, shaping simplicity and low manufacturing costs GFRP composites are used for a multitude of purposes—for car manufacturing, maritime vessels, oil and gas production, construction, sporting goods and more. Aircraft, [wind energy](#) and electronics are among the industries which use the GFRP most, with the global demand increasing annually by 6 percent.

"GFRP composites used for many industries including wind turbine blades manufacturing are either thermoset or thermoplastic. In either case, they roughly consist only of two components—fiber and resin (in some cases with different micro or nanoparticle additions). As for the fiber, it usually is [carbon fiber](#) or fiberglass (the latter is cheaper)," explains Dr. Yousef.

During the experiments, the research group were applying pyrolysis (in presence of zeolite catalysts and without) to different batches of composites—fiberglass thermoset and fiberglass thermoplastic—measured the extraction of phenol (the primary component in the production of phenolic resins and the manufacture of nylon and other synthetic fibers) in each case. After that, they were analyzing the basic raw materials from each batch. The researchers also assessed the effect that the additive nanoparticles (such as carbon black) can have on the yield of useful components.

Although the yield of the components extracted during pyrolysis differs depending on the temperatures applied, the proximate measurement revealed that in all the cases the numerous volatile compounds (up to 66 percent) and fiber residue (around 30 percent) were extracted. The added fiber nanoparticles (Carbon nanotubes and graphene) increased the yield of phenol.

"The volatile components are basically phenol, which can be used for further production of resin, and the fiber residue can have numerous

applications after purifying it chemically—for fiber-reinforced concrete, polymer composites, fiber flooring. Our method is virtually waste-free with some small emissions, which is standard in this kind of conversion operation," says Yousef.

Needs a real wind turbine blade to continue research

The experiments were conducted using the samples prepared at a laboratory that had compositions similar to those used for making wind turbine blades, and not the [wind turbine blades](#) themselves. Therefore, Dr. Yousef notes, there is a need to assess the effect of the paint coating, that the real turbine blades are covered with, to the results. However, he believes that it will not be significant.

"We would of course be happy to receive a worn-out wind turbine blade, which is no longer usable, and to conduct our experiments with the samples obtained from the real object," says Yousef.

At the moment, the research group is creating a model, which would allow to scale and calculate the wider economic and environmental impact of the results.

This study is one of the several conducted by the same research group, which focus on the practical implementations of the principles of the circular economy. Last year, their experiment of lint microfiber conversion into energy received broad international attention.

"We are developing research in numerous topics related to [climate change](#), extracting of clean energy (H₂ and CH₄) using membranes technology, and transition to the circular economy as these topics are closely related to the future of our planet," says Dr. Yousef.

More information: Samy Yousef et al, Catalytic pyrolysis kinetic

behaviour of glass fibre-reinforced epoxy resin composites over ZSM-5 zeolite catalyst, *Fuel* (2022). [DOI: 10.1016/j.fuel.2022.123235](https://doi.org/10.1016/j.fuel.2022.123235)

Provided by Kaunas University of Technology

Citation: Proposed method for wind turbine blade recycling (2022, March 15) retrieved 3 May 2024 from <https://techxplore.com/news/2022-03-method-turbine-blade-recycling.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.