

# Miniature permanent magnets can be printed on a 3D printer

October 17 2022

---



Miniature permanent magnets printed on a 3D printer. Credit: UrFU / Oksana Meleshchuk

Scientists from the Ural Federal University and the Ural Branch of the Russian Academy of Sciences are determining the optimal conditions for

3D printing of permanent magnets from hard magnetic compounds based on rare-earth metals. This will make it possible to start small-scale production of magnets, give them any shape during manufacturing, and create complex configurations of magnets. Such magnets are suitable for miniature electric motors and electric generators, on which pacemakers work. In addition, the technology minimizes production waste and has a shorter production cycle. A description of the method and experimental results are published in the *Journal of Magnetism and Magnetic Materials*.

Creating complex and small magnets is not an easy scientific and technical task, but they are in demand in various specialized applications, primarily medical ones. One of the most promising ways to create complex-shaped parts from magnetically hard materials is 3D printing. Scientists managed to determine the optimal parameters for 3D printing of [permanent magnets](#) using the selective laser sintering method.

This is an additive manufacturing method in which magnetic material in the form of powder is sintered layer by layer into a three-dimensional product of a given shape based on a previously created 3D model. This technology makes it possible to change the internal properties of the magnet at almost all stages of production. For example, to change the chemical composition of the compound, the degree of spatial orientation of crystallites and crystallographic texture, and to influence the coercivity (resistance to demagnetization).

"Producing small magnets is a difficult task. Now they are created only by cutting a large magnet into pieces, because of the mechanical processing about half of the used material turns into garbage. Also, cutting introduces a lot of defects in the near-surface layer, which causes the properties of the magnet to deteriorate enormously. Additive technologies allow to avoid this and make complex magnets, for example, with one [north pole](#) and two spatially separated south poles or a

magnet with five south poles and five north poles at once. Such configurations are necessary for pacemakers, where it is only possible to assemble the rotor for an electric motor from separate magnets under a microscope," explains Dmitry Neznakhin, Associate Professor at the Department of Magnetism and Magnetic Nanomaterials and Researcher at the Section of Solid State Magnetism at UrFU.



To print magnets, scientists pour special steel powder into the printer. Credit: UrFU / Oksana Meleshchuk

Currently, scientists succeeded in producing thin, about one millimeter, permanent magnets whose properties are similar to those of industrially produced magnets. The base was a powder containing samarium,

zirconium, iron, and titanium. The compound has suitable characteristics for permanent magnets, but traditional manufacturing methods deprive the compound of most of its properties. Therefore, the scientists decided to see if the properties could be preserved with the new technology.

"When creating permanent magnets based on these compounds using traditional methods, the properties of the finished products are far from the theoretically predicted ones. We found that when sintering a sample, adding a fusible powder from an alloy of samarium, copper, and cobalt allows the magnetic characteristics of the main magnetic powder to be retained. This alloy melts at temperatures lower than the properties of the main alloy change, which is why the final material retains its coercive force and density," adds Dmitry Neznakhin.

At the moment, scientists are establishing the basic laws of formation of the microstructure and magnetic properties of hard magnetic materials, and determining which magnetic materials can be used to manufacture permanent magnets using the laser sintering method. This includes testing how the sintering method affects the properties of another known base for magnets—an alloy of neodymium, iron, and boron. The next stage of the work will be the production of bulk permanent magnets suitable for practical applications.

**More information:** D.S. Neznakhin et al, Phase composition and magnetic properties of (Sm,Zr)Fe<sub>11</sub>Ti magnets produced by selective laser melting, *Journal of Magnetism and Magnetic Materials* (2022). [DOI: 10.1016/j.jmmm.2022.169937](https://doi.org/10.1016/j.jmmm.2022.169937)

Provided by Ural Federal University

Citation: Miniature permanent magnets can be printed on a 3D printer (2022, October 17)

retrieved 18 April 2024 from

<https://techxplore.com/news/2022-10-miniature-permanent-magnets-3d-printer.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.