


Developing a W-band receive module for ultra-low noise data transmission in satellite communications

December 12 2022



Similar RF module developed at Fraunhofer IAF. Credit: Fraunhofer Institute for Applied Solid State Physics IAF

To meet the world's rapidly growing data consumption and increasing bandwidth requirements, satellite communications are shifting to higher

frequencies. The W-band (75–110 GHz) is well suited for use in space, but technical components have been lacking so far.

For this reason, Fraunhofer IAF has launched the BEACON [project](#): Together with researchers from RPG-Radiometer Physics, a novel W-band receive front-end module is to be realized as part of the ESA ARTES program. The goal is to develop a technology that is lower in noise than any previous W-band amplifier module and thus enables the transfer of extremely high data rates through space.

Due to limited bandwidth, it is becoming increasingly difficult to meet the growing need for higher data rates in [satellite systems](#) with very high data throughput. Using higher frequencies can help to meet this increasing demand. The W-band (75–110 GHz) is well suited for satellite communication applications: Not only does it offer high data throughput when used at high altitudes and in space, but it is also likely to significantly increase system capacity, reduce the number of gateway earth stations, and thus reduce overall system costs. However, there has been a lack of suitable technology and hardware for applications in the W-band frequency range to date.

The Fraunhofer Institute for Applied Solid State Physics IAF, together with RPG Radiometer Physics GmbH, has taken up this challenge in the project "BEACON—W-band Integrated Active Receive Front-End": The project partners are developing an integrated active W-band receive frond-end with an operating frequency of 81 to 86 GHz that will enable extremely high data rates or long-distance data transmission with [low power consumption](#).

Minimal noise at high data throughput

The receive module is based on Fraunhofer IAF's extremely low-noise MMIC technology (MMIC—monolithic microwave integrated circuit).

"Fraunhofer IAF has done tremendous development work in the mHEMT process over the past years and has acquired a core competence in developing amplifiers with the lowest noise worldwide. Based on this, the project aims to reduce the noise figure to below 3.5 dB and thus significantly improve the state of the art," explains Dr. Philipp Neining, project coordinator and researcher at Fraunhofer IAF.

In addition, the receive module is designed to isolate left- from right-hand [circular polarization](#) and amplify them with two separate channels (LHCP and RHCP), which serves to effectively double data throughput.

A major challenge in the BEACON project is the novel arrangement of components on the very small module area. The new approach involves integrating a large number of functions within a very small footprint: These include the polarizer, waveguide transitions to two individual amplifiers, two coaxial output connectors and the associated DC circuitry. "The combination of these features—extremely low noise, two different polarizations and an innovative array—brings an enormous technological advance in the field of W-band components," Neining summarizes the project proposal.

W-band data transmission from space already successfully tested

Only last year, satellite signals in the W-band frequency range were received from space for the first time. The W-Cube nanosatellite began its journey to polar orbit aboard a Falcon 9 rocket in the summer of 2021 and has since been successfully transmitting satellite signals to Earth at 75 GHz from an altitude of 500 kilometers. For this mission, Fraunhofer IAF had already developed the transmitter module of the satellite as well as the receive [module](#) of the corresponding ground station.

Provided by Fraunhofer Institute for Applied Solid State Physics IAF

Citation: Developing a W-band receive module for ultra-low noise data transmission in satellite communications (2022, December 12) retrieved 30 May 2023 from <https://techxplore.com/news/2022-12-w-band-module-ultra-low-noise-transmission.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.