

Novel adaptation for existing blast furnaces could reduce steelmaking emissions by 90%

January 24 2023



Credit: Pixabay/CC0 Public Domain

Researchers from the University of Birmingham have designed a novel adaptation for existing iron and steel furnaces that could reduce carbon



dioxide (CO_2) emissions from the steelmaking industry by nearly 90%.

This radical reduction is achieved through a "closed loop" carbon recycling system, which could replace 90% of the coke typically used in current blast furnace-basic <u>oxygen</u> furnace systems and produces oxygen as a biproduct.

Devised by Professor Yulong Ding and Dr. Harriet Kildahl from the University of Birmingham's School of Chemical Engineering, the system is detailed in a paper published in the *Journal of Cleaner Production*, which shows that if implemented in the U.K. alone, it could deliver <u>cost</u> <u>savings</u> of £1.28 billion in five years while reducing overall U.K. emissions by 2.9%.

Professor Ding said, "Current proposals for decarbonizing the steel sector rely on phasing out existing plants and introducing electric arc furnaces powered by <u>renewable electricity</u>. However, an electric arc furnace plant can cost over £1 billion to build, which makes this switch economically unfeasible in the time remaining to meet the Paris Climate Agreement. The system we are proposing can be retrofitted to existing plants, which reduces the risk of stranded assets, and both the reduction in CO_2 , and the cost savings, are seen immediately."

Most of the world's steel is produced via blast furnaces which produce iron from <u>iron ore</u> and basic oxygen furnaces which turn that iron into steel.

The process is inherently carbon intensive, using metallurgical coke produced by destructive distillation of coal in a coke oven, which reacts with the oxygen in the hot air blast to produce carbon monoxide. This reacts with the <u>iron</u> ore in the furnace to produce CO_2 . The top gas from the furnace contains mainly nitrogen, CO and CO_2 , which is burned to raise the air blast temperature up to 1,200 to 1,350 degrees Celsius in a



hot stove before blown to the furnace, with the CO_2 and N_2 (also containing NO_x) emitted to the environment.

The novel recycling system captures the CO_2 from the top gas and reduces it to CO using a crystalline mineral lattice known as a "perovskite" material. The material was chosen as the reactions take place within a range of temperatures (700–800 degrees Celsius) that can be powered by <u>renewable energy sources</u> and/or generated using heat exchangers connected to the blast furnaces.

Under a high concentration of CO_2 , the perovskite splits CO_2 into oxygen, which is absorbed into the lattice, and CO, which is fed back into the <u>blast</u> furnace. The perovskite can be regenerated to its original form in a chemical reaction that takes place in a low oxygen environment. The oxygen produced can be used in the basic oxygen <u>furnace</u> to produce steel.

Iron and steelmaking is the biggest emitter of CO_2 of all foundation industrial sectors, accounting for 9% of global emissions. According to the International Renewable Energy Agency (IRENA), it must achieve a 90% reduction in emissions by 2050 to limit global warming to 1.5 degrees Celsius.

More information: Harriet Kildahl et al, Cost effective decarbonisation of blast furnace—basic oxygen furnace steel production through thermochemical sector coupling, *Journal of Cleaner Production* (2023). DOI: 10.1016/j.jclepro.2023.135963

Provided by University of Birmingham

Citation: Novel adaptation for existing blast furnaces could reduce steelmaking emissions by



90% (2023, January 24) retrieved 27 April 2024 from <u>https://techxplore.com/news/2023-01-blast-furnaces-steelmaking-emissions.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.