

## Efficient and scalable moisture-electric generators made from ionic hydrogel

February 27 2023



Schematic and electric output characteristics of IHMEG. a) The structure of one single IHMEG device with asymmetric-moisture penetration layers. The material consists of PA-gelated hydrogel. b) The schematic diagram of the asymmetric moisture stimulus-induced potential in IHMEG. c) The continuous DC Voc output (red curve) of an IHMEG device over time under open ambient environment. The ambient relative humidity (blue curve) and temperature (black curve) were synchronously recorded. Credit: Wiley Online Library



Finding a simple and efficient green energy conversion technology is an essential component of the plan to achieve carbon neutrality and sustainable green energy while also satisfying the increased demand for electrical power.

A moisture-electric generator (MEG), which uses <u>chemical energy</u> from <u>atmospheric moisture</u> to generate electricity directly without causing pollutants and harmful gas emissions, is an emerging technology in the energy field.

## **Practical green power source**

However, most MEGs suffer from intermittent electrical signals and low currents. In addition, large-scale integration and practical applications have not yet been achieved. To address these problems, Prof. Xiaoming Tao, Director of Research Institute for Intelligent Wearable Systems, and her team have created a novel and efficient ionic hydrogel moisture-electric generator (IHMEG) that is versatile, flexible, lightweight and has all-weather adaptable features. The research is published in the journal *Advanced Materials*.

The IHMEG operates stably in a wide range of environmental conditions from 10% to 85% relative humidity (RH) and from -24°C to 60°C. This provides a promising green <u>power source</u> for Hong Kong, where most of the RH fluctuates from 40% to 90% during the year.

## **Applicable energy source**

Thanks to the synergistic effect of the moisture-absorption capability and fast ion transport capability in the ionic hydrogel network, a single IHMEG unit of 0.25 cm<sup>2</sup> can continuously generate direct-current electricity with a constant open-circuit voltage of  $\approx 0.8$  V for more than



1,000 hours, a high short-current density of 0.24 mA cm<sup>-2</sup>, and power density of up to 35  $\mu$ W cm<sup>-2</sup>.



The applications of IHMEGs as a direct power source. a) Demonstration of  $1 \times 5$  serial IHMEG package as a power-supplying source for directly driving an electronic calculator. b) Schematic of the circuit design and working demonstration of the self-powered electronic ink screen by IHMEG device with  $3 \times 5$  series-parallel connection. The circuit primarily consists of three elements:



electronic ink screen, electricity supply using the integrated IHMEG devices, and a single-chip computer to input the display message. c) The serial "POLYU" LEDs directly driven by integrated IHMEGs. d) Wearable demonstration of  $1 \times$ 5 serial IHMEG package as energy watchband to power an electronic watch, which normally uses button battery CR2032. e) Electro-deposition of Nickle millimeter-level structure by  $5 \times 5$  IHMEGs device: i) Schematic plot of the setup for the Ni electroplating by using  $5 \times 5$  IHMEGs. ii) SEM image and EDS mapping of the deposited nickel pattern. iii) The work voltage and current between the cathode and anode. Credit: Wiley Online Library

Importantly, the large-scale integration of IHMEG units can be readily achieved and offers a device with a voltage up to 210 V, which is capable of directly driving numerous commercial electronics, including electronic calculators, energy watchbands, electronic ink screens and light-emitting-diode arrays. Also, the IHMEG power device is successfully employed to electroplate metal nickel (Ni) structures on the millimeter scale. This is a significant advance and proves the practical application of scalable IHMEG with sufficient energy.

Moreover, an IHMEG direct-circuit (DC) power source can be easily designed and fabricated by connecting multiple IHMEG units in serial, parallel fashion or a combination of these according to operating requirements. With the progress in spontaneous energy generation from ubiquitous moisture, the IHMEG device shows great potential to develop versatile, efficient, scalable and green <u>power</u> sources for self-powered IoT and wearable electronics systems.



The underlying mechanism of IHMEG. 2D-FTIR correlation spectra in the 3700–3000 cm–1 wavenumber region: a) synchronous; b) asynchronous contour maps for IHMEG samples when exposing in the air. The pink area and blue area denote the positive and negative correlation peaks, respectively. c) The water diffusion difference between the top and the bottom surface of hydrogel by 2D Raman mapping after 120 min. d) Photos of the experiment for visualizing the dynamic change of the moisture-induced ionic diffusion process. A piece of the hydrogel is sandwiched between the open ends of two cylindrical containers, the upper tube has two open ends and the bottom one has one open end and one closed end. They are filledwith bromophenol blue/isopropanol solution. Water is added into the upper tube through the open end. The color change in the two tubes indicates the dynamic diffusion of dissociated protons with water diffusion. e) Schematic plot of the setup for the Kelvin probe force microscope



(KPFM) test and f) the potential change of hydrogel. A piece of hydrogel (250  $\mu$ m thickness) absorbed moisture from one side and the other side was covered without wetting. The potentials of the two sides are detected by KPFM. The scan range is 5 × 5  $\mu$ m. The lower right picture shows the potential increment of the hydrogel after water diffusion from the wetting side to non-wetting side from 15 to 30 min. g) The proposed mechanism of moisture-induced ionic diffusion process. Credit: Wiley Online Library



Power devices by integration of IHMEG units in serial or parallel packages as a practical DC source for commercial low-power electronics. a) Voltage output of a serial IHMEG units with different series number. The test condition is 65% RH. b) The Voc related to the serial number of device units. Inset is the equivalent circuit scheme of serial IHMEG units. c) The picture of the voltage output of flexible IHMEG with 130 units in series. d) Current output of a single IHMEG package with different parallel number. e) The Isc related to the parallel number of device units. Inset is the equivalent circuit of the parallel IHMEG package. f) Voltage–time curve of a commercial capacitor with 47  $\mu$ F directly charged by a serial IHMEG units with 1, 4, and 8 units. Credit: Wiley Online Library



**More information:** Su Yang et al, Ionic Hydrogel for Efficient and Scalable Moisture-Electric Generation, *Advanced Materials* (2022). <u>DOI:</u> <u>10.1002/adma.202200693</u>

Provided by Hong Kong Polytechnic University

Citation: Efficient and scalable moisture-electric generators made from ionic hydrogel (2023, February 27) retrieved 1 May 2024 from <u>https://techxplore.com/news/2023-02-efficient-scalable-moisture-electric-generators-ionic.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.