

Food safety: Cleaning with plasma instead of chemicals

June 7 2023



Investigation of microbial contamination of conveyor belts. Credit: Jessica Lietze

A new method for cleaning conveyor belts in food production can replace the widely used disinfection chemicals. Plasma-treated water is effective against microbial contamination at a shorter exposure time and



degrades without environmentally hazardous traces. These results were recently published in the journal *Innovative Food Science and Emerging Technologies*.

Microbial contamination can occur along the entire food processing chain. In order to minimize <u>health risks</u> for consumers, all <u>production</u> <u>processes</u> must be carried out safely. It is therefore common practice to clean conveyor belts with disinfectants, for example in vegetable or meat processing. However, the processes should not only ensure <u>food safety</u>, but also be environmentally friendly and sustainable.

A team of researchers from science and industry has therefore developed a new method that uses plasma-treated water to clean food conveyor belts instead of the amine-based disinfectants commonly used in the industry.

To produce plasma treated water, plasma treated air is injected into distilled or tap water. Plasma-treated water thus contains many reactive nitrogen and oxygen species such as nitrous acid (HNO_2), nitrogen monoxide (NO^*) and ozone (O_3), which occur naturally and which degrade without leaving traces that are harmful to the environment, but overall have a high antimicrobial efficiency

The scientists examined the use of plasma-treated water in comparison to common washing processes using the example of residues from minced meat and Braeburn apples on silicone and PVC conveyor belts. The cleaning process usually included pre-cleaning with water (20 bar, <u>room temperature</u>) and mild, fat-dissolving foam, spraying with the active substance and subsequent cleaning of the belts with tap water. As a result, the use of plasma-treated water reduced the number of germs just as efficiently as an amine-based disinfectant (by >3 log10 CFU/cm²), and with a significantly shorter inactivation time of just one minute compared to 15 minutes with conventional cleaning.



In order to monitor the cleaning success, an RGB color sensor system was also developed for the automated detection of food residues on the belts. "Actually, it's about the microbial colonization on the conveyor belts, which can become a health hazard. In practice, however, monitoring the microorganisms would be too time-consuming and expensive, especially since they only develop on the organic residues," explains Dr. Julia Durek, scientist at the Leibniz Institute for Agricultural Engineering and Bioeconomy in Potsdam. "We therefore tested the sensor system for detecting food residues. The optical system works very quickly and precisely detects even the smallest of residues. It is easy to use and can therefore be implemented for automated hygiene monitoring in food production."

Dr. Julia Durek is reflecting further optimization options. "The slightly higher number of germs found on silicone belts, which have a slightly rougher surface than PVC belts, show that in the future we should pay more attention to damaged or aged conveyor belts. In the indentations of rough spots, microorganisms may survive an application of plasmaprocessed water. In addition, especially with <u>animal products</u>, the use of warm or hot water could provide a better fat-dissolving effect and thus also an additional decontamination benefit."

More information: Julia Durek et al, Optimized cleaning of conveyor belts using plasma-processed water assisted by optical detection of food residues, *Innovative Food Science & Emerging Technologies* (2023). DOI: 10.1016/j.ifset.2023.103379

Provided by Leibniz-Institut für Agrartechnik und Bioökonomie e.V. (ATB)

Citation: Food safety: Cleaning with plasma instead of chemicals (2023, June 7) retrieved 4 May



2024 from https://techxplore.com/news/2023-06-food-safety-plasma-chemicals.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.