

# Researchers develop low-cost sensor to enhance robots' sense of touch

July 27 2023

paper clip



Fx: 	Force (N):
Fy: 	Fx: -0.945
Fz: 	Fy: 0.215
	Fz: -2.510

tape



Fx: 	Force (N):
Fy: 	Fx: -1.335
Fz: 	Fy: -0.052
	Fz: -5.765

ball



Fx: 	Force (N):
Fy: 	Fx: -1.427
Fz: 	Fy: 0.000
	Fz: -5.658

empty can



Fx: 	Force (N):
Fy: 	Fx: -2.055
Fz: 	Fy: 0.159
	Fz: -7.502

The sensor feeling the objects. Credit: F-TOUCH Team

Achieving human-level dexterity during manipulation and grasping has been a long-standing goal in robotics. To accomplish this, having a reliable sense of tactile information and force is essential for robots. A recent study, published in *IEEE Robotics and Automation Letters*, describes the L3 F-TOUCH sensor that enhances the force sensing capabilities of classic tactile sensors. The sensor is lightweight, low-cost,

and wireless, making it an affordable option for retrofitting existing robot hands and graspers.

The human hand can sense pressure, temperature, texture, and pain. Additionally, the human hand can distinguish between objects based on their shape, size, weight, and other physical properties. Many current [robot hands](#) or graspers are not even close to [human hands](#) as they do not have integrated haptic capabilities, complicating handling objects.

Without knowledge about the interaction forces and the shape of the handled object, the robot fingers would not have any "feel of touch," and objects could easily slip out of the robot hand's fingers or even be crushed if they are fragile.

The study, led by Professor Kaspar Althoefer of Queen Mary University of London, presents the new L3 F-TOUCH—high-resolution fingertip sensor, where L3 stands for Lightweight, Low-cost, wireLess communication. The sensor can measure an object's geometry and determine the forces to interact with it. Unlike other sensors that estimate interaction forces via tactile information acquired by camera images, the L3 F-TOUCH measures interaction forces directly, achieving higher measurement accuracy.

"In contrast to its competitors that estimate experienced interaction forces through reconstruction from camera images of the deformation of their soft elastomer, the L-3 F-TOUCH measures interaction forces directly through an integrated mechanical suspension structure with a mirror system achieving higher measurement accuracy and wider measurement range."

"The sensor is physically designed to decouple force measurements from geometry information. Therefore, the sensed three-axis force is immuned from contact geometry compared to its competitors. Through

embedded [wireless communications](#), the sensor also outperforms competitors with regards to integrability with robot hands," says Professor Kaspar Althoefer.

When the sensor touches the surface, a compact suspension structure enables the elastomer—a rubber-like material that deforms to measure high-resolution contact geometry exposed to an external force—to displace upon contact. To make sense of this data, the elastomer's displacement is tracked by detecting the movement of a special marker, a so-called ARTag, allowing us to measure contact forces along the three major axes (x, y, and z) via a calibration process.

"We will focus our future work on extending the sensor's capabilities to measure not only force along the three major axes but also rotational forces such as twist, which could be experienced during screw fastening while remaining accurate and compact. These advancements can enable the sense of touch for more dynamic and agile robots in manipulation tasks, even in human-[robot](#) interaction settings, like for patient rehabilitation or physical support of the elderly," adds Professor Althoefer.

This breakthrough could pave the way for more advanced and reliable robotics in the future, as with the L3 F-TOUCH sensor, robots can have a sense of touch, making them more capable of handling objects and performing complex manipulation tasks.

**More information:** Wanlin Li et al, L<sup>3</sup> F-TOUCH: A Wireless GelSight With Decoupled Tactile and Three-Axis Force Sensing, *IEEE Robotics and Automation Letters* (2023). [DOI: 10.1109/LRA.2023.3292575](#)

Provided by Queen Mary, University of London

Citation: Researchers develop low-cost sensor to enhance robots' sense of touch (2023, July 27) retrieved 21 February 2024 from <https://techxplore.com/news/2023-07-low-cost-sensor-robots.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.