

Target therapy for buried interface improves efficiency of perovskite solar cells

July 31 2023, by Li Yuan



Credit: CC0 Public Domain

Perovskite solar cells (PSCs) are promising in the photovoltaic market due to their advantages of high performance, low cost and easy fabrication of large-scale flexible devices.



Tin dioxide (SnO_2) is a commonly used electron transport material for ni-p-type PSCs due to its high light transmittance and electron mobility, suitable energy levels, good stability under UV irradiation, and it can be processed at low temperatures. The buried interface of perovskite/SnO₂ plays a crucial role in achieving <u>high efficiency</u> and stability. However, the non-exposed buried interface is challenging to study and manipulate.

Researchers led by Dr. JI Xiaofei from Shanghai Advanced Research Institute (SARI) of the Chinese Academy of Sciences, with collaborators from the Southern University of Science and Technology and the City University of Hong Kong, have reported a facile and effective strategy for precisely modulating the buried interface through incorporating formamidine oxalate (FOA) in a colloidal SnO₂ -based electrontransporting layer. The results were published in *Advanced Materials* on July 17.

They found that both formamidinium (FA^+) and oxalate ions showed longitudinal gradient distribution in the SnO₂ layer, and mostly accumulated at the SnO₂ /perovskite buried interface. The modified SnO₂ exhibited higher Fermi level, which induces better energy level alignment between perovskite and SnO₂ -FOA, and helps avoid carrier accumulation at the interface and improves open-circuit voltage.

Moreover, the FOA could modulate crystal growth of upper perovskite films, which enables high-quality perovskite films with minimized grain boundaries and superior interface contacts.

 FA^+ cations and oxalate anions could suppress <u>oxygen vacancies</u> and tin interstitial defects on the SnO₂ surface and $FA^+/Pb2^+$ associated defects at the perovskite buried interface contemporaneously, which contribute to achieve target defect passivation. Ultimately, the FOA-modified buried <u>interface</u> increased the record power conversion efficiency to 25.05% with enhanced stability of corresponding devices under light,



heat, and moisture conditions.

More information: Xiaofei Ji et al, Target Therapy for Buried Interface Enables Stable Perovskite Solar Cells with 25.05% Efficiency, *Advanced Materials* (2023). DOI: 10.1002/adma.202303665

Provided by Chinese Academy of Sciences

Citation: Target therapy for buried interface improves efficiency of perovskite solar cells (2023, July 31) retrieved 11 May 2024 from <u>https://techxplore.com/news/2023-07-therapy-interface-efficiency-perovskite-solar.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.