

## Novel model helps analyze phase transition heat transfer in heat pipes



August 16 2023, by Zhang Nannan

Schematic diagram and calculation results of heat pipes. Credit: Liu Jian

A research group led by Prof. Yu Dali from the Hefei Institutes of Physical Science of the Chinese Academy of Sciences (CAS), together with researchers from the City University of Hong Kong, has developed a transient 3D computational fluid dynamics model to investigate the



liquid-vapor flow and heat transfer for a water heat pipe under various non-uniform loads. The study was published in *Annals of Nuclear Energy*.

Heat pipes are highly efficient heat transfer devices that utilize the phase transition of a working fluid to achieve high-flux heat transfer. Compared to conventional metals, the heat transfer efficiency of heat pipes is tens or even hundreds of times higher. As a result, heat pipes have found applications in various fields that require high-density <u>heat</u> transfer, including heat export from the core of small solid-state reactors, radiative radiators, fusion reactor divertors, and advanced electronic components.

In this study, the researchers developed the 3D transient heat pipe model using FLUENT software. The model was validated by comparing its results with <u>experimental data</u> obtained under both uniform and non-uniform heating conditions. The comparison showed an <u>error rate</u> of up to 4.73%.

With this model, the circumferential flow characteristics of the heat pipe at the wick region under non-uniform heating conditions were observed for the first time using numerical methodology.

What's more, the researchers examined how the length of the adiabatic section, the heating power, and the heating range affected the thermalhydraulic properties of the heat pipe when it was loaded in different ways.

They found that the heat pipe started up much faster when the heating power was increased or the length of the adiabatic section was reduced. They proved that lowering the circumferential heating range didn't change the start-up time.



In addition, uneven heating power in the horizontal direction caused the spot on the wall with the highest temperature to tilt toward the spot with the highest power. On the other hand, when the heat pipe was heated evenly, the temperature on the wall was the lowest.

"Our results provide valuable theoretical support and <u>analytical tools</u> for further research and development of high-profile <u>heat pipes</u>," said Prof. Yu Dali.

**More information:** Jian Liu et al, Numerical analysis of transient heat and mass transfer for a water heat pipe under non-uniform heating conditions, *Annals of Nuclear Energy* (2023). <u>DOI:</u> <u>10.1016/j.anucene.2023.110036</u>

Provided by Chinese Academy of Sciences

Citation: Novel model helps analyze phase transition heat transfer in heat pipes (2023, August 16) retrieved 11 May 2024 from https://techxplore.com/news/2023-08-phase-transition-pipes.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.