

Combination of stressors key to testing perovskite solar cells, research finds

September 12 2023



Perovskite solar cells should be subjected to a combination of stress tests simultaneously to best predict how they will function outdoors, according to researchers at the U.S. Department of Energy's National



Renewable Energy Laboratory (NREL).

Solar cells must endure a set of harsh conditions—often with variable combinations of changing stress factors—to judge their stability, but most researchers conduct these tests indoors with a few fixed stressing conditions. While these tests provide some necessary insight, understanding which stressor applied during indoor tests provided predictive correlations with outdoor operation is critical.

"We must understand how well perovskite solar cells will perform outdoors, under real conditions, to move this technology closer to commercialization," said Kai Zhu, a senior scientist in the Chemistry and Nanoscience Center at NREL. "That's why we identified accelerated testing protocols that can be conducted in the laboratory to reveal how these cells would function after six months in operation outside."

Zhu is lead author of a new paper, "<u>Towards linking lab and field</u> <u>lifetimes of perovskite solar cells</u>," published in the journal *Nature*. His co-authors from NREL are Qi Jiang, Robert Tirawat, Ross Kerner, E. Ashley Gaulding, Jimmy Newkirk, and Joseph Berry. Other co-authors are from the University of Toledo, who have collaborated with Zhu on several other recent papers about perovskites.

Outdoor conditions, such as humidity, heat, and even light, put stress on solar cells. As a result, the efficiency of solar cells declines and power production decreases over time. To reach the reliability targets for commercialization of perovskite technology, protocols must first be established so that improvements from different groups can be easily validated and compared.

Researchers tend to test the stability of <u>perovskite solar cells</u> by exposing them to light and under low temperatures. However, a broad range of testing conditions exist, making it challenging to compare different



studies and discern their relevance to achieving the reliability needed for commercialization.

The NREL-led research team put perovskite <u>solar cells</u> through a battery of tests. During the test for operational stability, the cells retained more than 93% of their maximum efficiency after about 5,030 hours of continuous operation. The cells were subjected to thermal cycling, with temperatures repeatedly fluctuating between -40°C and 85°C. After 1,000 cycles, the cells showed an average of about 5% degradation.

The tests addressed different stressors, such as light and heat, separately. However, in real-world conditions, these individual factors act simultaneously to affect solar cell performance. When combined, for example, light and heat significantly accelerate performance degradation or cause new problems that were otherwise absent or occurring at slower rates when testing separately.

The researchers concluded that high temperature and illumination is the most critical combination of stressors for understanding how well a <u>perovskite</u> solar cell will perform outdoors.

More information: Qi Jiang et al, Towards linking lab and field lifetimes of perovskite solar cells, *Nature* (2023). <u>DOI:</u> <u>10.1038/s41586-023-06610-7</u>

Provided by National Renewable Energy Laboratory

Citation: Combination of stressors key to testing perovskite solar cells, research finds (2023, September 12) retrieved 15 May 2024 from <u>https://techxplore.com/news/2023-09-combination-stressors-key-perovskite-solar.html</u>



This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.