

A multilayered design strategy for highefficiency thin crystalline silicon solar cells

September 27 2023



High-performance 20-µm-thin crystalline silicon (c-Si) solar cell design uses much less silicon. Figures from the report by Xie et al. include (left) a semifinished c-Si cell on a flexible steel substrate; (middle) a complete cell; (right) image of a fabricated thin c-Si cell showing its flexibility. Credit: *Journal of Photonics for Energy* (2023). DOI: 10.1117/1.JPE.13.035501

Solar power has become indispensable in our global pursuit of clean energy and sustainability. Today, about 95% of solar cells are made using crystalline silicon (c-Si). Most commercial designs employ a c-Si photoactive layer with a thickness of around 160–170 μ m. However,



since silicon alone makes up nearly half the cost of each solar panel, experts believe that next-generation c-Si solar cells will be much thinner.

Unfortunately, despite a few recent improvements, the conversion efficiency of thin c-Si solar cells still lags far behind that of thick industrial ones. This problem stems from the fact that the best design strategies for thin c-Si cells only maximize individual parameters, such as short-circuit <u>current density</u>, open-circuit voltage, or fill factor. None of the current methods can simultaneously improve these parameters, all of which are important for realizing <u>high efficiency</u>.

Against this backdrop, a research team from Hangzhou Dianzi University, China, has developed a new strategy to achieve remarkable efficiency improvements in thin c-Si solar cells. Their study, <u>published</u> <u>the Journal of Photonics for Energy</u>, represents a significant breakthrough in the field of silicon solar cell technology.

The proposed strategy optimizes a few key optical and electrical characteristics, which the team identified to be responsible for the differences in the reported conversion efficiencies of thick and thin c-Si solar cells. Using commercial software programs, they ran optical simulations of various thin cell designs. Through further experiments using solar cells, the researchers arrived at an innovative fabrication methodology that offers several advantages over conventional techniques.

Instead of using the silicon ingot cutting approach typically used to manufacture thick c-Si layers, the team employed a layer transfer method. They used hydrofluoric acid to etch pores into a thick silicon wafer. This porous layer served as a substrate to grow a 20- μ m-thin monocrystalline silicon layer, which could be easily detached and transferred onto a flexible stainless-steel substrate.



To enhance the optical and electrical performance of the thin silicon layer, the researchers deposited multiple metal nanofilms on both sides using plasma-enhanced chemical vapor deposition— $SiO_2/SiN_x/SiO_x$ layers and $Al_2O_3/SiN_x/SiO_x$ layers with a pyramidal texture on the sides facing the front and rear of the solar cell, respectively.

The front SiN_x/SiO_x and rear SiO_x/SiN_x layers increased the light absorption of the silicon layer in the shorter and longer wavelengths, respectively. This, in turn, enhanced the short-circuit current density—a measure of the number of charge carriers that can be generated and collected by the solar cell. Compared with a standard solar cell used as reference, the current density increased from 34.3 to 38.2 mA/cm².

Furthermore, the SiO₂ and Al₂O₃ layers provided high surface passivation, minimizing the recombination and loss of generated charge carriers. This led to a higher open-circuit voltage—a measure of the maximum voltage generated by a solar cell. It was boosted from 632 mV in the reference cell to 684 mV when using the proposed design. Consequently, the fill factor of the solar cell, an indicator of how close a solar cell operates to its theoretical maximum efficiency, increased from 76.2 to 80.8%.

As confirmed by both simulations and experiments, the proposed strategy resulted in an enhancement of conversion efficiency from 16.5 to 21.1%, a remarkable gain of 4.6% (corresponding to an approximately 28% improvement, compared to the reference cell). This puts the efficiency of thin c-Si solar cells close to that of their industrial thick counterparts, which today clocks in at 24%.

JPE Associate Editor Leonidas Palilis, Professor of Condensed Matter Physics at University of Patras, Greece, remarks, "Overall, the findings of this study present a novel way to realize high-performance thin <u>crystalline silicon solar cells</u> using much less silicon—for a 20-µm cell,



around one eighth of the amount required for a thick 160- μ m cell on a given panel size."

This advance will likely contribute to more widespread cost-effective adoption of <u>silicon solar power</u> technology, due to the reduced cost and the concomitant expansion of the solar panel manufacturing capacity.

More information: Guanglin Xie et al, Investigation on significant efficiency enhancement of thin crystalline silicon solar cells, *Journal of Photonics for Energy* (2023). DOI: 10.1117/1.JPE.13.035501

Provided by SPIE

Citation: A multilayered design strategy for high-efficiency thin crystalline silicon solar cells (2023, September 27) retrieved 12 May 2024 from https://techxplore.com/news/2023-09-multilayered-strategy-high-efficiency-thin-crystalline.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.