

## This 3D printer can watch itself fabricate objects

November 19 2023



A new high-throughput, multimaterial 3D inkjet printer uses computer vision to rapidly and automatically control the amount of material being printed in realtime. This rendering shows a robot being built layer-by-layer using the process. The black spheres represent the material that the printer uses. The material is then cured by UV light, represented in blue. At the top of the image are the cameras that scan the procedure and adjust accordingly. Credit: Moritz Hocher



With 3D inkjet printing systems, engineers can fabricate hybrid structures that have soft and rigid components, like robotic grippers that are strong enough to grasp heavy objects but soft enough to interact safely with humans.

These multimaterial 3D printing systems utilize thousands of nozzles to deposit tiny droplets of resin, which are smoothed with a scraper or roller and cured with UV light. But the smoothing process could squish or smear resins that cure slowly, limiting the types of materials that can be used.

Researchers from MIT, the MIT spinout Inkbit, and ETH Zurich have developed a new 3D inkjet printing system that works with a much wider range of materials. Their printer utilizes computer vision to automatically scan the 3D printing surface and adjust the amount of resin each nozzle deposits in real time to ensure no areas have too much or too little material.

Since it does not require mechanical parts to smooth the resin, this contactless system works with materials that cure more slowly than the acrylates which are traditionally used in 3D printing. Some slower-curing material chemistries can offer improved performance over acrylates, such as greater elasticity, durability, or longevity.

In addition, the automatic system makes adjustments without stopping or slowing the printing process, making this production-grade printer about 660 times faster than a comparable 3D inkjet printing system.

The researchers used this printer to create complex, robotic devices that combine soft and rigid materials. For example, they made a completely 3D-printed robotic gripper shaped like a human hand and controlled by a set of reinforced, yet flexible, tendons.



"Our key insight here was to develop a machine vision system and completely active feedback loop. This is almost like endowing a printer with a set of eyes and a brain, where the eyes observe what is being printed, and then the brain of the machine directs it as to what should be printed next," says co-corresponding author Wojciech Matusik, a professor of electrical engineering and computer science at MIT who leads the Computational Design and Fabrication Group within the MIT Computer Science and Artificial Intelligence Laboratory (CSAIL).

He is joined on the paper by lead author Thomas Buchner, a doctoral student at ETH Zurich, co-corresponding author Robert Katzschmann, Ph.D. '18, assistant professor of robotics who leads the Soft Robotics Laboratory at ETH Zurich; as well as others at ETH Zurich and Inkbit. The research will appear in *Nature*.

## **Contact free**

This paper builds off a low-cost, multimaterial 3D printer known as <u>MultiFab</u> that the researchers introduced in 2015. By utilizing thousands of nozzles to deposit tiny droplets of resin that are UV-cured, MultiFab enabled high-resolution 3D printing with up to 10 materials at once.

With this new project, the researchers sought a contactless process that would expand the range of materials they could use to fabricate more complex devices.

They developed a technique, known as vision-controlled jetting, which utilizes four high-frame-rate cameras and two lasers that rapidly and continuously scan the print surface. The cameras capture images as thousands of nozzles deposit tiny droplets of resin.

The <u>computer vision</u> system converts the image into a high-resolution depth map, a computation that takes less than a second to perform. It



compares the depth map to the CAD (computer-aided design) model of the part being fabricated, and adjusts the amount of resin being deposited to keep the object on target with the final structure.



Researchers produced a functional, tendon-driven robotic hand that has 19 independently actuatable tendons, soft fingers with sensor pads, and rigid, load-bearing bones. Credit: Wojciech Matusik, Robert Katzschmann, Thomas Buchner, et al

The automated system can make adjustments to any individual nozzle. Since the printer has 16,000 nozzles, the system can control fine details of the device being fabricated.



"Geometrically, it can print almost anything you want made of multiple materials. There are almost no limitations in terms of what you can send to the printer, and what you get is truly functional and long-lasting," says Katzschmann.

The level of control afforded by the system enables it to print very precisely with wax, which is used as a support material to create cavities or intricate networks of channels inside an object. The wax is printed below the structure as the device is fabricated. After it is complete, the object is heated so the wax melts and drains out, leaving open channels throughout the object.

Because it can automatically and rapidly adjust the amount of material being deposited by each of the nozzles in real time, the system doesn't need to drag a mechanical part across the print surface to keep it level. This enables the printer to use materials that cure more gradually, and would be smeared by a scraper.

## **Superior materials**

The researchers used the system to print with thiol-based materials, which are slower-curing than the traditional acrylic materials used in 3D printing. However, thiol-based materials are more elastic and don't break as easily as acrylates. They also tend to be more stable over a wider range of temperatures and don't degrade as quickly when exposed to sunlight.

"These are very important properties when you want to fabricate robots or systems that need to interact with a real-world environment," says Katzschmann.

The researchers used thiol-based materials and wax to fabricate several complex devices that would otherwise be nearly impossible to make with



existing 3D printing systems. For one, they produced a functional, tendon-driven robotic hand that has 19 independently actuatable tendons, soft fingers with sensor pads, and rigid, load-bearing bones.

"We also produced a six-legged walking robot that can sense objects and grasp them, which was possible due to the system's ability to create airtight interfaces of soft and rigid materials, as well as complex channels inside the structure," says Buchner.

The team also showcased the technology through a heart-like pump with integrated ventricles and artificial heart valves, as well as metamaterials that can be programmed to have non-linear material properties.

"This is just the start. There is an amazing number of new types of materials you can add to this technology. This allows us to bring in whole new material families that couldn't be used in 3D printing before," Matusik says.

The researchers are now looking at using the system to print with hydrogels, which are used in tissue-engineering applications, as well as silicon materials, epoxies, and special types of durable polymers.

They also want to explore new application areas, such as <u>printing</u> customizable medical devices, semiconductor polishing pads, and even more complex robots.

More information: Robert Katzschmann, Vision-controlled jetting for composite systems and robots, *Nature* (2023). DOI: 10.1038/s41586-023-06684-3. www.nature.com/articles/s41586-023-06684-3

This story is republished courtesy of MIT News



(<u>web.mit.edu/newsoffice/</u>), a popular site that covers news about MIT research, innovation and teaching.

Provided by Massachusetts Institute of Technology

Citation: This 3D printer can watch itself fabricate objects (2023, November 19) retrieved 10 May 2024 from <u>https://techxplore.com/news/2023-11-3d-printer-fabricate.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.