

Processing biochar into pellets to offset emissions in concrete production

January 8 2024



a) C-LWA produced in the pelletization process in a rotating pan concrete mixer,b) C-LWA in the cured (hardened) state and c) C-LWA pellet embedded in concrete (cut section). Credit: *Journal of Cleaner Production* (2023). DOI:



10.1016/j.jclepro.2023.140008

To achieve the goal of a climate-neutral Switzerland by 2050, strategies and processes with a negative CO_2 balance are necessary. These socalled negative emission technologies (NET) are intended to counterbalance the remaining "hard-to-avoid" emissions in 2050 and should help ensure that we eventually achieve net zero.

As one of the main emitters, the <u>construction sector</u> has a particular obligation. About 8% of <u>global greenhouse gas emissions</u> are caused by <u>cement production</u>. At the same time, initial efforts are emerging to use the construction sector, with its massive consumption of resources, as a possible carbon sink.

What sounds paradoxical will succeed if we start "building with CO_2 "—or rather, using carbon to produce <u>building materials</u> and thus removing it from the atmosphere in the long term. For such visions to become reality, a great deal of research is needed—such as is currently being done at Empa's Concrete & Asphalt lab. A team led by Pietro Lura is developing a process for integrating <u>biochar</u> into concrete.

Difficulties due to porosity

Biochar is produced by a pyrolytic carbonization process of biomass in the absence of oxygen and consists of a high level of pure carbon—the carbon that the plants have extracted from the atmosphere in the form of CO_2 as they grow. While CO_2 is emitted when plants are burned, it remains bound in the biochar over the long term.

The first concrete products with integrated biochar are already on the market. However, biochar is often introduced into the concrete



untreated, which can lead to difficulties. "Biochar is very porous and therefore not only absorbs a lot of water, but also expensive admixtures used in concrete production," explains Empa researcher Mateusz Wyrzykowski.

"Moreover, it is difficult to handle and not completely harmless either." The fine coal dust is problematic for the <u>respiratory tract</u> and carries a certain risk of explosion.

For these reasons, the researchers propose in a paper that has just been published in the *Journal of Cleaner Production* the processing of the biochar into <u>pellets</u>. "Such lightweight aggregates already exist from other materials such as expanded clay or fly ash. The knowhow in handling these materials is available in industry, and this increases the chances that the concept will be put into practice," says Wyrzykowski.

Net zero at 20% share

To produce the pellets, the team used a concrete mixer with a rotating pan in which they mixed the biochar with water and cement and, as a result of the rotation, obtained small pellets with a diameter of between 4 and 32 millimeters. In turn, they used these pellets to produce normal concrete of strength classes C20/25 to C30/37—the classes that are most widely used in civil engineering today.

"With a proportion of 20% by volume of carbon pellets in the concrete, we achieve net zero emissions," says Mateusz Wyrzykowski. That is, the amount of carbon stored offsets all the emissions produced in the production of both the pellets and the concrete. While the limit has probably not yet been reached for normal concrete (density between 2,000 and 2,600 kg/m³) with 20% by volume, the negative emission potential is particularly striking for lightweight concrete (density approx. 1,800 kg/m³): An admixture of 45% by volume of carbon pellets in the



concrete leads to total negative emissions of $-290 \text{ kg CO}_2/\text{m}^3$. By comparison, conventional concrete emits around 200 kg CO₂/m³.

Carbon from the atmosphere

For laboratory head Pietro Lura, research in his lab is a crucial contribution to achieving climate targets. He does not see biochar, which has served as a model material in current research, as the most important source of carbon. Rather, he draws attention to the broad concept "Mining the Atmosphere," which several labs at Empa are pursuing: The production of synthetic methane using solar energy, water and CO_2 from the atmosphere in sunny regions of the world, and the subsequent pyrolysis of the synthetic gas.

"This yields hydrogen, which can be used as an energy carrier in industry or mobility, and solid <u>carbon</u>, which we can process into pellets—like biochar—and incorporate into concrete," explains Lura.

More information: Mateusz Wyrzykowski et al, Cold-bonded biocharrich lightweight aggregates for net-zero concrete, *Journal of Cleaner Production* (2023). DOI: 10.1016/j.jclepro.2023.140008

Provided by Swiss Federal Laboratories for Materials Science and Technology

Citation: Processing biochar into pellets to offset emissions in concrete production (2024, January 8) retrieved 9 May 2024 from <u>https://techxplore.com/news/2024-01-biochar-pellets-offset-emissions-concrete.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is



provided for information purposes only.