

How extreme weather and system aging affect the US photovoltaic fleet

January 25 2024, by Harrison Dreves



Credit: Dennis Schroeder, NREL

For photovoltaic (PV) systems—designed to operate over lifetimes of 20, 30, or even 50 years—small losses in energy production can add up to measurable differences over time. These differences can even determine whether a system operates at a profit or loss. Yet, small changes in energy production are frustratingly difficult to measure, especially in the noisy and often incomplete data of a PV system's production.



After four years of work, National Renewable Energy Laboratory (NREL) researchers have compiled a dataset from an unprecedented number of PV systems across the United States—<u>data streams</u> from 25,000 inverters across almost 2,500 commercial- and utility-scale PV sites in 37 states and U.S. territories. By cleaning and averaging data from a huge set of systems, the PV Fleet Performance Data Initiative (PV Fleet) offers a clearer-than-ever look at the health of the U.S. PV fleet and reveals some of the factors that are impacting its performance.

The work is **<u>published</u>** in the IEEE Journal of Photovoltaics.

Long-term degradation of US PV systems matches expectations

The performance of all solar panels is expected to degrade over time due to exposure to the elements. However, a range of factors drives degradation and the average rate of PV performance loss, which is often debated.

In 2022, in their <u>first major finding</u>, the PV Fleet team found a national median loss in performance of 0.75%/year, confirming similar values reported by previous studies that analyzed smaller datasets. Additionally, the new analysis discovered that systems in hotter temperature zones exhibited about twice as much performance loss as those in cooler climates (0.88%/year and 0.48%/year loss, respectively).

"This median loss in performance is a crucial number," said Chris Deline, a group manager for PV field performance at NREL and author on the PV Fleet publications. "First, it shows that our fleet of PV systems, on the whole, is not failing catastrophically, but rather degrading at a modest rate within expectations. It's important that we quantify this rate as accurately as we can, because this small but tangible



number is used in almost all financing agreements that fund solar projects and provides critical guidance for the industry."

Extreme weather's frequency is increasing, but how big is its impact?

Extreme <u>weather</u> events—flooding, <u>high winds</u>, hail, wildfire, and lightning—can damage fielded PV systems and certainly contribute to long-term performance loss. But how large of an impact does extreme weather have across PV systems in the United States, and are the impacts seen more in the short term or long term?

In the new paper, researchers used the scale of the PV Fleet dataset to quantify some impacts of extreme weather. By comparing the performance of systems in the PV Fleet dataset against a National Oceanic and Atmospheric Administration (NOAA) map of <u>extreme</u> <u>weather events</u>, the researchers studied how each system's performance was affected when an extreme weather event occurred within 10 kilometers of its location.

For most systems, short-term impact of extreme weather is minimal

Overall, the short-term outages caused by extreme weather—such as outages due to PV modules being disturbed by <u>strong winds</u> or inverters being damaged by flooding—have a minimal impact on most systems. Over the 2008–2022 time range studied, the PV Fleet team found that the median outage length after an extreme weather event was two to four days, resulting in only a 1% median loss in annual performance. A very small number (12 systems out of 6,400) experienced much longer outages of two weeks or more.

Most outages occurred because of flooding and rain, followed by wind



events. And most systems in the dataset only experienced one weatherrelated outage.

When powerful enough, extreme weather accelerates long-term degradation

Short-term outages and production losses are not the only impact of extreme weather. Mechanical stresses from wind, hail, and snow can lead to cracked cells within PV modules and other forms of PV system degradation.

A clear trend emerged in the long-term performance of PV systems after exposure to extreme weather events. After weather events above certain thresholds—hail greater than 25 millimeters (1 inch) in diameter, winds in excess of 90 kilometers/hour (56 miles/hour), or snow depths greater than 1 meter—systems showed greater annual performance losses. Below these thresholds, systems experienced performance losses similar to the PV Fleet average.

Even systems composed of modules qualified through International Electrotechnical Commission (IEC) 61215—the industry standard that includes a test for resistance to impact by 25-millimeter-diameter hail—showed higher performance loss rates when exposed to that same size hail in natural settings. This suggests a need for more stringent hail testing (and such a standard is currently under development, published as technical specification IEC TS 63397 in 2022).

Systems damaged by winds above 90 kilometers/hour also displayed an interesting trend, with parts of some systems avoiding damage, possibly due to site-specific phenomena such as wind shadowing from adjacent structures, which helps reduce wind speeds.



Best practices for the PV industry to counter extreme weather's impact

"We don't feel any of this analysis suggests that PV systems are unreliable or especially vulnerable to extreme weather," said Dirk Jordan, a distinguished member of research staff at NREL and author on the PV Fleet publications. "PV has demonstrated that it can provide backup power and save lives when surrounding infrastructure is damaged by extreme weather events. Yet, there are further measures we can take to improve the quality of equipment and especially installation <u>best</u> <u>practices</u> to increase resilience to these weather events."

To harden PV systems against the impacts of extreme weather, module manufacturers and PV testing organizations need to first understand the thresholds at which damage can occur. Then, the industry can begin to design for these conditions and—crucially—create tests that subject panels to realistic stresses. The recent development of a new hail testing specification is a good step in this direction, but more rigorous testing standards for wind and snow loading should also be considered.

"High-quality installations are also key to increasing resilience against extreme weather. Standardizing installation practices, such as using through-bolting and mounting modules far enough from the edge of roofs in wind-prone areas, could help mitigate system performance impacts," Jordan said. Several best practices guidelines to increase PV system resilience to storm damage and hail damage have been collected on the U.S. Department of Energy's website and in an <u>NREL fact sheet</u>.

Those who operate and maintain PV systems should also be aware of the extreme weather thresholds reported in these PV Fleet publications so they know when to further analyze impacted systems. And companies that provide PV system insurance may want to support new, more robust



tests, especially in regions with the fastest-growing rates of <u>extreme</u> <u>weather</u>.

Finally, the industry should be aware that recent trends, such as larger modules, thinner cells, and thinner front glass, may increase system vulnerability if not designed and tested appropriately. Harmonizing operations and maintenance records and closely monitoring PV assets will enable proactive detection of potential degradation caused by new module designs.

Unique dataset enables new insights

The new findings were only possible due to the unique scale and data quality of PV Fleet. Numerous PV system operators submitted detailed system data to NREL on the condition that it would be anonymized. In exchange for contributing data to the PV Fleet dataset, system operators received customized analyses of their systems' performance.

The project has collected 25,000 inverter data streams from almost 2,500 commercial and utility PV sites—representing more than 8 gigawatts of the 72-gigawatt U.S. solar fleet. The mean age of systems in the dataset is five years.

The PV Fleet team considered data on module technology, system size, and geographical location, as well as operations and maintenance records. Data cleaning and quality assurance were key, requiring extensive human review and machine learning to filter out shifts in weather, interruptions in data feeds, and quirks in system operation.

More information: Dirk C. Jordan et al, Extreme Weather and PV Performance, *IEEE Journal of Photovoltaics* (2023). DOI: <u>10.1109/JPHOTOV.2023.3304357</u>



Provided by National Renewable Energy Laboratory

Citation: How extreme weather and system aging affect the US photovoltaic fleet (2024, January 25) retrieved 9 May 2024 from <u>https://techxplore.com/news/2024-01-extreme-weather-aging-affect-photovoltaic.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.