

Innovative coating prevents limescale formation

February 12 2024, by Peter Rüegg



Test set-up with which the researchers tested how lime crystals adhere to different surfaces. Credit: Julian Schmid / ETH Zurich



Hot water tanks, washing machines, kettles: limescale forms in every domestic appliance that comes into contact with (hot) water—especially in areas where the water is hard, meaning high in calcium. Often the only thing that helps is to use vinegar or a special descaler to dissolve the rock-hard deposits and restore the appliance's functionality.

This is a nuisance in households—and an expensive problem in thermal power stations, for example those that generate electricity, where the formation of limescale is known as fouling.

Heat exchangers are particularly prone to limescale, which greatly reduces the efficiency of the systems: a layer of limescale just one millimeter thick in the heat exchanger's pipes reduces the efficiency of electricity production by approximately 1.5 percent. To compensate for these losses an additional 8.7 million metric tons of hard coal would have to be burned. That's bad for the <u>carbon footprint</u> and the climate, and it's expensive for the electricity producers.

Innovative limescale-repellent surface

A research team from ETH Zurich and the University of California, Berkeley has now found a possible solution to this problem: a special limescale-repellent coating with microscopically small ridges that prevent the adhesion of limescale crystals. The team's study was <u>published</u> in the journal *Science Advances*.

Fundamental research into the development of limescale-repellent surfaces has been sparse. So the researchers, led by former ETH Professor Thomas Schutzius, took a close look at the interactions among individual growing limescale crystals, the surrounding water flow and the surface at the microscopic level.

Based on this, Schutzius' doctoral student Julian Schmid and other team



members developed several coatings from various soft materials and tested them in the lab at ETH Zurich.



Test object polystyrene beads on the grooved surface. Credit: Julian Schmid / ETH Zurich

Hydrogel with microstructure is most effective

The most effective coating turned out to be a polymer hydrogel, the surface of which is covered in tiny ridges thanks to microtextured molds, which the researchers fabricated using photolithography.



The hydrogel's microstructure is reminiscent of natural models such as shark scales, which also have a ribbed structure to suppress fouling on the sharks' skin.

In kettles or boilers, the riblets ensure that the limescale crystals have less contact with the surface, meaning they can't adhere and are thus easier to remove; water flowing over the hydrogel and through the ribbed structure carries them away. While the coating can't fully prevent limescale crystals from forming, the constant passive removal of the microscopic crystals stops them growing together to form a tenacious layer.

In producing the different coatings, the researchers primarily varied the polymer content. The lower the polymer content and the higher the <u>water</u> <u>content</u>, the less well the calcium carbonate crystals adhere to the surface.

Tests with model particles made of polystyrene show that the coating's surface structures must be smaller than the particles that are deposited on it. This reduces the contact surface and thus the adhesive force. "We varied the material's surface structure to achieve the greatest efficiency, then carried out the crystal experiments with this optimum structure size," Schmid says.

The team's experiments show that the hydrogel coating is very effective: when water flowed across the hydrogel-coated surface, on which limescale crystals with a size of around 10 micrometers had previously been grown, up to 98 percent of the crystals were removed.





Only a few micrometer-sized lime crystals on the grooved surface under the electron microscope. Credit: Julian Schmid / ETH Zurich

Eco-friendly solution

The researchers emphasize that their solution is more eco-friendly and more efficient than existing approaches to descaling, some of which involve toxic and aggressive chemicals. In contrast, the hydrogel is biocompatible and environmentally friendly. The technology behind this solution should also be scalable: the coating could be applied in various ways that are already in use in industry today.



Rather than applying for a patent for their development, the researchers have deliberately decided in favor of publication in a scientific journal. This means that all interested parties are free to further develop and utilize the new <u>coating</u>.

More information: Julian Schmid et al, Imparting scalephobicity with rational microtexturing of soft materials, *Science Advances* (2023). <u>DOI:</u> <u>10.1126/sciadv.adj0324</u>

Provided by ETH Zurich

Citation: Innovative coating prevents limescale formation (2024, February 12) retrieved 10 May 2024 from <u>https://techxplore.com/news/2024-02-coating-limescale-formation.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.