

A strategy to suppress strain propagation in ultrahigh-Ni cathodes during fast charging

March 25 2024, by Ingrid Fadelli



The design principle and structures of epitaxial entropy-assisted coating. a, Schematic illustrations of the entropy-assisted surface design for ultrahigh-Ni cathodes. The oriented attachment-driven phase transformation under thermal equilibrium of Wadsley–Roth nanocrystals and layered structure can induce epitaxial entropy-assisted coating layer formation on the NCM surface, achieving good cathode anti-corrosion and anti-cracking tolerances with fast ion transportation. b, In situ HEXRD during heating of Ni90 (L), nanoNb₁₂WO₃₃ (WR) and nano-ZrO₂ (ZrO2) with equal weight ratio. Pink dashed boxes indicate pristine layer phase. White dashed boxes indicate emerging new peaks. c, HAADF–TEM and corresponding EDS element mappings of EEC–Ni90. d, Highresolution TEM image and fast Fourier transform patterns of selected region i (red) and ii (orange). The layer outside the EEC layer is Au for the purpose of protecting samples during focused ion beam TEM sample preparation. Credit: *Nature Energy* (2024). DOI: 10.1038/s41560-024-01465-2

To meet the growing demand of the electronics industry and support the widespread deployment of electric vehicles, researchers will need to develop increasingly advanced and highly performing battery technologies. A promising approach for boosting the performance of lithium-ion batteries (LiBs) entails the use of nickel (Ni)-rich layered oxides as cathode materials.

These Ni-rich cathodes can have numerous advantages, for instance increasing the capacity of batteries, improving their rate capabilities and lowering their overall fabrication costs. Nonetheless, studies so far have also highlighted their limitations, ranging from capacity degradation and structural instability during fast-charging and long-term cycling.

Researchers at Argonne National Laboratory and other institutes worldwide recently introduced a strategy that could improve the structural stability and reliability of ultrahigh-Ni cathodes. This strategy, outlined in a paper <u>published</u> in *Nature Energy*, entails the use of epitaxial entropy-assisted oxide coating to suppress strain propagation, the process that typically underpins the cathodes' structural deterioration during battery fast-charging and prolonged cycling.

"Surface reconstruction and the associated severe strain propagation have long been reported as the major cause of cathode failure during fast charging and long-term cycling," Chen Zhao, Chuanwei Wang and their



collaborators wrote in their paper. "Despite tremendous attempts, no known strategies can simultaneously address the electrochemomechanical instability without sacrificing energy and <u>power</u> <u>density</u>.

"We report an epitaxial entropy-assisted coating strategy for ultrahigh-Ni $\text{LiNi}_x\text{Co}_y\text{Mn}_{1-x-y}\text{O}_2$ (x ≥ 0.9) cathodes via an oriented attachment-driven reaction between Wadsley–Roth phase-based oxides and the layered-oxide cathodes."

Essentially, Zhao, Wang and their colleagues designed a specialized oxide coating that aligns with the structure of Ni-rich cathodes. In addition to enhancing the robustness of the <u>cathode materials</u>' surface, these coatings can enhance ionic conductivity, consequently supporting the fast charging of batteries.

The team's coating is based on Wadsley-Roth crystallographic shear phases, a class of compounds that have been found to boost the performance of electrodes in LiBs, Notably, these compounds were found to adhere better to Ni-rich cathodes, strengthening their structural stability during prolonged operation and fast-charging.

"The high anti-cracking and anti-corrosion tolerances as well as the fast ionic transport of the entropy-assisted surface effectively improved the fast charging/discharging capability, wide temperature tolerance and thermal stability of the ultrahigh-Ni cathodes," Zhao, Wang and their colleagues wrote.

"Comprehensive analysis from the primary and secondary particle level to the electrode level using multi-scale in situ synchrotron X-ray probes reveals greatly reduced lattice dislocations, anisotropic lattice strain and oxygen release as well as improved bulk/local <u>structural stability</u>, even when charging beyond the threshold state of charge (75%) of layered



cathodes."

The researchers evaluated their proposed coating strategy in a series of experiments, where they coated Ni-rich layered cathodes and then tested their performance over time and under different conditions. Their findings were highly promising, as their approach significantly reduced damage to cathodes, even during fast-charging and after many operation cycles.

"We expect that such an epitaxial entropy-assisted <u>coating</u> strategy will open up surface engineering opportunities for the design and development of high-energy and high-power LiBs and beyond," the researchers concluded in their paper.

More information: Chen Zhao et al, Suppressing strain propagation in ultrahigh-Ni cathodes during fast charging via epitaxial entropy-assisted coating, *Nature Energy* (2024). DOI: 10.1038/s41560-024-01465-2

© 2024 Science X Network

Citation: A strategy to suppress strain propagation in ultrahigh-Ni cathodes during fast charging (2024, March 25) retrieved 15 May 2024 from <u>https://techxplore.com/news/2024-03-strategy-suppress-strain-propagation-ultrahigh.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.