

# Novel technologies for transforming wind turbine and power grid stability control

March 13 2024

---



Credit: Pixabay/CC0 Public Domain

Researchers from the University of Birmingham, U.K., are working on novel ways of preventing threats to grid stability that can result in the loss of power to millions of people, equipment damage, and limited

power transfer capability.

With increasing reliance on renewables, global installations of wind farms have increased rapidly. However, two major technological issues remain—power system frequency control and forced oscillations, which can cause widespread disruption over entire power grids.

Professor Xiao-Ping Zhang, Chair in Electrical Power Systems at Birmingham's Department of Electronic, Electrical, and Systems Engineering, whose research focuses on developing advanced technologies for smart grids, has developed technologies to overcome these challenges.

The University of Birmingham Enterprise has filed [patent applications](#) covering the technologies and is seeking commercial partners for licensing, collaboration, or co-development.

Shifts in supply and demand cause grid frequency events. When demand exceeds supply, the grid's frequency drops to a "frequency nadir," and with a frequency second dip before recovery to a settled grid state. This grid-settling process can be protracted, with a consequent loss of efficiency and revenue for the operator.

Professor Zhang's novel method quickens this recovery and eliminates the risk of frequency second dip, with minimal (less than 1%) loss of wind power capture.

It was developed for use in variable-speed wind turbine systems (WTSs), which have emerged as the dominant type of wind turbine system. These systems usually operate at maximum power point tracking (MPPT) mode to extract the greatest amount of energy and so do not regulate their active power to support the grid when its frequency deviates from its usual value.

This [new method comprises a control system](#), which has been simulated in six scenarios with different [wind speeds](#) and wind power penetration levels. These simulations showed the system arrests the primary frequency dip, raises frequency to a high level that is close to the settling frequency within 20 seconds, and completely eliminates the risk of the secondary [frequency](#) dip.

The system can be easily integrated into existing wind turbine control systems and has a non-communication-based central design, which means that links with other turbines and the grid are not required for it to function.

The second technology [addresses the issue of forced oscillations](#), which occur when external disturbances produce oscillations that are close to or equal to the natural oscillations in a power system.

In the context of wind farms, they are triggered by factors such as [wind shear](#), wind turbulence, and upstream turbine wakes and cause reduced output and equipment damage. If unchecked, they can spread to the grid, with widespread and catastrophic consequences. In the context of power grids, FOs are caused by malfunctioning equipment and can result in large oscillations thousands of miles away from the source.

Here, Professor Zhang has devised a control system that can be implemented in WTSs that can suppress and isolate forced oscillations originating either from the grid or the WTS itself.

The system, which releases or absorbs power that is opposite to the oscillating power, has been verified by simulations with constant or varying wind speeds, different wind farm locations with respect to the source of FOs, on the modified two-area and IEEE 39-bus power systems (which represent the aggregation of a large number of generators), using a [real-time](#) digital simulator and a physical modeling

and simulation tool.

The results of these simulations showed that the system can suppress and isolate forced oscillations originating either from the grid or the WTS itself. The loss of wind power capture was negligible, and in addition to suppressing forced oscillations, the simulations showed the system also helps to dampen the intrinsic natural oscillations.

Professor Zhang said, "With increasing high penetration of renewable energy generation moving towards 100%, exploitation of future control potential from wind turbines becomes inevitable. These two technologies make the most of this potential, to benefit both the [grid](#) and wind farm operators, and ultimately energy users who need an uninterrupted energy supply and hence bring significant added values to wind turbines and power grids."

Details of the method have been previously published in two papers in the *IEEE Open Access Journal of Power and Energy*.

**More information:** Xianxian Zhao et al, Fast Frequency Support From Wind Turbine Systems by Arresting Frequency Nadir Close to Settling Frequency, *IEEE Open Access Journal of Power and Energy* (2020). [DOI: 10.1109/OAJPE.2020.2996949](https://doi.org/10.1109/OAJPE.2020.2996949).

Xianxian Zhao et al, Isolation and Suppression of Forced Oscillations Through Wind Farms Under Grid Following and Grid Forming Control, *IEEE Access* (2021). [DOI: 10.1109/ACCESS.2021.3082166](https://doi.org/10.1109/ACCESS.2021.3082166)

Provided by University of Birmingham

Citation: Novel technologies for transforming wind turbine and power grid stability control (2024, March 13) retrieved 8 May 2024 from <https://techxplore.com/news/2024-03-technologies-turbine-power-grid-stability.html>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.