

## **Coordinate-wise monotonic transformations enable privacy-preserving age estimation with 3D face point cloud**

April 23 2024





Four elementary monotonic functions (exponential, logarithmic, square, and sine) were applied immediately after Coordinate-Wise Rank Transformation (CRT) and normalized to [-1, 1] in a coordinate-wise manner. The three circles on the radar plot correspond to the first-order Model Indistinguishability, the second-order Model Indistinguishability and the Mean Absolute Error of the exp(CRT) model (the largest among the four), from the inside out. All models could accurately and consistently estimate ages. Credit: Science China Press

In a recent <u>publication</u> in *Science China Life Sciences*, a research team led by Professor Jing-Dong Jackie Han and Ph.D. student Xinyu Yang from Peking University established a deep learning model for age estimation using non-registered 3D face point clouds. They also proposed the coordinate-wise monotonic transformation algorithm to isolate agerelated facial features from identifiable human faces.

The team trained the model on over 16,000 instances of 3D face point cloud data, achieving an average absolute error of about 2.5 years. The model recognizes the rotational invariance of human faces. In their analysis of face shape and skin tone's importance, they developed the coordinate-wise monotonic transformations <u>algorithm</u>.

The algorithm can distort faces without changing the relative positions of facial elements. The team found that the deep learning models could accurately and consistently estimate ages with faces before and after applying the <u>transformation</u> algorithm in various scenarios, demonstrating that the transformations effectively preserve age-related facial features.

However, in visual tests, subjects experienced a notable decrease in



accuracy and response speed when assessing transformed faces. Additionally, computational face verification models trained on normal face shapes failed to recognize transformed faces.

Considering the similarities and differences in age estimation and identification tasks, the research team proposed a facial data protection guideline. This guideline, featuring coordinate-wise monotonic transformations and selective data provisioning, aims to provide a theoretical foundation for managing facial data centers or public datasets.



Points 1, 2, 3, 4 originally had irregular ascending y-coordinates, which were transformed and rescaled to an arithmetic progression from -1 to 1 by coordinate-wise ranking (a special case of Coordinate-Wise Monotonic Transformations) and normalization. Points 2 and 4 originally shared the same x-coordinate, and they continued to do so after CRT. Credit: Science China Press

## More information: Xinyu Yang et al, Coordinate-wise monotonic



transformations enable privacy-preserving age estimation with 3D face point cloud, *Science China Life Sciences* (2024). DOI: 10.1007/s11427-023-2518-8

## Provided by Science China Press

Citation: Coordinate-wise monotonic transformations enable privacy-preserving age estimation with 3D face point cloud (2024, April 23) retrieved 21 May 2024 from https://techxplore.com/news/2024-04-wise-monotonic-enable-privacy-age.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.