

Stable high-energy density lithium-ion batteries could lead to fast charging electric vehicles

May 31 2024



Phenomenon of irreversible lithium plating occurring in bare graphite anodes for lithium ion batteries after fast charged cycling test



 $Al_2O_3\mathcal{-}coated$ KERI graphite anodes for lithium-ion batteries that suppresses the irreversible lithium plating even after fast charged cycling test

The cross-sectional SEM images of the cycled bare anode and Al_2O_3 -coated anode for lithium ion battery. (left). Credit: Korea Electrotechnology Research Institute (KERI)

A research team has developed a core technology to ensure the charging/discharging stability and long-life of lithium-ion batteries under fast-charging conditions. Their <u>findings were published</u> in *Advanced Functional Materials*.



A crucial prerequisite for the widespread adoption of electric vehicles (EVs) is the enhancement of lithium-ion battery performance in terms of driving range and safety. Fast charging is also essential for user convenience. However, increasing the energy density of <u>lithium-ion</u> <u>batteries</u> necessitates thicker electrodes, which can lead to battery degradation and performance deterioration during rapid charging.

To address this issue, the KERI team discovered a solution by partially coating the surface of the anode of the lithium-ion battery with aluminum oxide (Al_2O_3) particles smaller than 1 micrometer. While many researchers worldwide have concentrated on the materials within the electrode, such as introducing functional nanotechnology into anode materials like graphite, Dr. Choi's team employed a straightforward processing technique to coat the electrode's surface with aluminum oxide.

Low in cost, excellent in electrical insulation and heat resistance, chemically stable, and possessing good mechanical properties, aluminum oxide is widely used in various ceramics.





Aluminum oxide dispersion (left) and anode for lithium ion battery coating it on. Credit: Korea Electrotechnology Research Institute (KERI)

The KERI researchers found that aluminum oxide particles effectively control the interface between the anode and the electrolyte in lithium-ion batteries, forming an interfacial highway for efficient Li⁺ transport. This prevents the electrodeposition of lithium (an irreversible change that makes the lithium unavailable for additional charging and discharging)



during fast charging, thereby ensuring the stability and lifespan of the lithium-ion battery during charging and discharging.

Another advantage of this technology is that it enables an increase in the energy density of lithium-ion batteries. Introducing other functional materials into the electrode's interior to improve performance and stability often complicates the synthesis process and reduces the amount of reversible lithium (initial coulombic efficiency). It also increases the electrode thickness, leading to performance deterioration under fast charging conditions.

However, the KERI technology involves surface treatment of the graphite anode, rather than modifying the interior active graphite materials. This approach achieves stable performance even under fast charging conditions for high-energy-density thick-film electrodes without a loss in the amount of reversible lithium.





KERI researchers are partially coating aluminum oxide on the surface of the anode of a lithium-ion battery. Credit: Korea Electrotechnology Research Institute (KERI)





KERI Dr. Choi Jeong Hee is holding an aluminum oxide dispersion (left) and the anode for a lithium-ion battery coating it on the anode. Credit: Korea Electrotechnology Research Institute (KERI)

Through various tests, the team confirmed that the high-energy-density anode coated with <u>aluminum oxide</u> (4.4 mAh/cm²) exhibits world-class performance, maintaining more than 83.4% of its capacity (residual capacity ratio) even after 500 cycles of rapid charging. They have verified this performance with pouch cells of up to 500mAh. The team



is now planning to scale up the technology to make it applicable to largearea, medium- to large-capacity cells.

The research team was led by Dr. Choi Jeong Hee at the Korea Electrotechnology Research Institute (KERI) Battery Materials and Process Research Center, in cooperation with a Hanyang University team mentored by Professor Lee Jong-Won and a Kyunghee University team mentored by Professor Park Min-Sik.

"Convenient fast charging and the energy density of lithium-ion batteries have long been considered a trade-off, which has hindered the widespread adoption of electric vehicles," said Dr. Choi. "Our work will help develop stable, high-energy-density lithium-ion batteries capable of fast charging. This advancement will contribute to the wider adoption of EVs and support the achievement of national carbon neutrality."

Patents have been registered in both Korea and the United States.

More information: Jeong-Hee Choi et al, Multi-Interface Strategy for Electrode Tailoring Toward Fast-Charging Lithium-Ion Batteries, *Advanced Functional Materials* (2024). DOI: 10.1002/adfm.202400414

Provided by National Research Council of Science and Technology

Citation: Stable high-energy density lithium-ion batteries could lead to fast charging electric vehicles (2024, May 31) retrieved 23 June 2024 from <u>https://techxplore.com/news/2024-05-stable-high-energy-density-lithium.html</u>

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.