

Artificial eye: Researchers combine metalens with an artificial muscle

February 23 2018




Photo of the metalens (made of silicon) mounted on a transparent, stretchy polymer film, without any electrodes. The colorful iridescence is produced by the large number of nanostructures within the metalens. Credit: Harvard SEAS

Inspired by the human eye, researchers at the Harvard John A. Paulson School of Engineering and Applied Sciences (SEAS) have developed an adaptive metalens, that is essentially a flat, electronically controlled

artificial eye. The adaptive metalens simultaneously controls for three of the major contributors to blurry images: focus, astigmatism, and image shift.


The research is published in *Science Advances*.

"This research combines breakthroughs in artificial muscle technology with metalens technology to create a tunable metalens that can change its focus in real time, just like the human eye," said Alan She, a graduate student at SEAS and first author of the paper. "We go one step further to build the capability of dynamically correcting for aberrations such as astigmatism and image shift, which the human eye cannot naturally do."

"This demonstrates the feasibility of embedded optical zoom and autofocus for a wide range of applications including cell phone cameras, eyeglasses and virtual and augmented reality hardware," said Federico Capasso, Robert L. Wallace Professor of Applied Physics and Vinton Hayes Senior Research Fellow in Electrical Engineering at SEAS and senior author of the paper. "It also shows the possibility of future optical microscopes, which operate fully electronically and can correct many aberrations simultaneously."

The Harvard Office of Technology Development has protected the intellectual property relating to this project and is exploring commercialization opportunities.

To build the [artificial eye](#), the researchers first needed to scale-up the metalens.



The adaptive metalens focuses light rays onto an image sensor. An electrical signal controls the shape of the metalens to produce the desired optical wavefronts (shown in red), resulting in better images. In the future, adaptive metalenses will be built into imaging systems, such as cell phone cameras and microscope, enabling flat, compact autofocus as well as the capability for simultaneously correcting optical aberrations and performing optical image stabilization, all in a single plane of control. Credit: Second Bay Studios/Harvard SEAS

Prior metalenses were about the size of a single piece of glitter. They focus light and eliminate spherical aberrations through a dense pattern of nanostructures, each smaller than a wavelength of light.

"Because the nanostructures are so small, the density of information in each [lens](#) is incredibly high," said She. "If you go from a 100 micron-sized lens to a centimeter sized lens, you will have increased the information required to describe the lens by ten thousand. Whenever we tried to scale-up the lens, the file size of the design alone would balloon up to gigabytes or even terabytes."

To solve this problem, the researchers developed a new algorithm to shrink the file size to make the metalens compatible with the technology currently used to fabricate integrated circuits. In a paper recently published in *Optics Express*, the researchers demonstrated the design and fabrication of metalenses up to centimeters or more in diameter.

"This research provides the possibility of unifying two industries: semiconductor manufacturing and lens-making, whereby the same technology used to make computer chips will be used to make metasurface-based optical components, such as lenses," said Capasso.

Next, the researchers needed to adhere the large metalens to an artificial muscle without compromising its ability to focus light. In the [human eye](#), the lens is surrounded by ciliary muscle, which stretches or compresses the lens, changing its shape to adjust its focal length. Capasso and his team collaborated with David Clarke, Extended Tarr Family Professor of Materials at SEAS and a pioneer in the field of engineering applications of dielectric elastomer actuators, also known as artificial muscles.

The researchers chose a thin, transparent dielectric elastomer with low loss - meaning light travels through the material with little scattering - to attach to the lens. To do so, they needed to develop a platform to transfer and adhere the lens to the soft surface.

"Elastomers are so different in almost every way from semiconductors that the challenge has been how to marry their attributes to create a novel multi-functional device and, especially how to devise a manufacturing route," said Clarke. "As someone who worked on one of the first scanning electron microscopes (SEMs) in the mid 1960's, it is exhilarating to be a part of creating an optical microscope with the capabilities of an SEM, such as real-time aberration control."

The elastomer is controlled by applying voltage. As it stretches, the position of nanopillars on the surface of the lens shift. The metalens can be tuned by controlling both the position of the pillars in relation to their neighbors and the total displacement of the structures. The researchers also demonstrated that the lens can simultaneously focus, control aberrations caused by astigmatism, as well as perform image shift.

Together, the lens and muscle are only 30 microns thick.

"All optical systems with multiple components - from cameras to microscopes and telescopes - have slight misalignments or mechanical stresses on their components, depending on the way they were built and their current environment, that will always cause small amounts of astigmatism and other aberrations, which could be corrected by an adaptive optical element," said She. "Because the adaptive metalens is flat, you can correct those aberrations and integrate different optical capabilities onto a single plane of control."

Next, the researchers aim to further improve the functionality of the lens and decrease the voltage required to control it.

More information: "Adaptive metalenses with simultaneous electrical control of focal length, astigmatism, and shift" *Science Advances* (2018). advances.sciencemag.org/content/4/2/eaap9957

Provided by Harvard John A. Paulson School of Engineering and Applied Sciences

Citation: Artificial eye: Researchers combine metalens with an artificial muscle (2018, February 23) retrieved 25 April 2024 from https://techxplore.com/news/2018-02-artificial-eye-combine-metalens-muscle_1.html

This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.