

# How the road network determines traffic capacity

19 November 2019, by Michael Keller



Rosengartenstrasse, Zurich. It is now possible to use a city's infrastructure to estimate the number of cars it can handle before congestion starts to build up. Credit: Keystone/Ennio Leanza

ETH researchers have shown that we can use the structure of urban road networks to predict their traffic capacity. This information enables urban and transportation planners to quantify how changes will influence traffic volumes.

People who commute by car will have an idea of what "traffic capacity" means, drawn from their own experience: as a stream of cars heads into a city early in the morning, the flow of traffic initially increases—until a critical point is reached in terms of the number of vehicles on the roads. From this point on, every additional car reduces the flow of traffic, and vehicles come to a standstill or form a traffic jam. This critical point represents a city's traffic capacity, or its possible maximum traffic volume.

The number of vehicles a road [network](#) can support differs from city to city, and the factors that influence these differing traffic capacities were previously unquantified. ETH researchers led by Kay Axhausen, Professor of Traffic and Transport Planning, and Professor Monica Menendez (now at New York University Abu Dhabi) have now used

billions of traffic measurements to reveal a set of rules that enable us to easily estimate the critical number of vehicles, and by extension, the traffic capacity of a city's road network.

## Analysis of traffic data from 41 cities

For their study in the journal *Scientific Reports*, the researchers looked at billions of vehicle observations from stationary traffic detectors in 41 cities around the world, including Tokyo and Los Angeles, as well as numerous European hubs such as Paris, London, Zurich, Basel, Bern and Lucerne. Once the scientists had simplified the enormous datasets and put them into a usable form, they started by calculating each city's individual traffic capacity. They focused on cars, explicitly excluding other forms of transport.

They subsequently compared the cities' traffic capacities and looked for characteristics that could explain the differences between them. As a result, they discovered that certain topological features relating to the road system and bus network could explain around 90 percent of the differences in traffic capacity that they observed between the various cities.

## Four characteristic network variables

The researchers led by Axhausen and Menendez identified four factors that shape a city's road network and ultimately define its traffic capacity: the road network density (measured in kilometers of lanes per surface area), and the redundancy of the network in providing alternative routes for getting to a particular destination. The frequency of traffic lights also had an impact, as did the density of bus and tram lines that compete with vehicular traffic for both space and rights of way (such as signal priority or bus lanes, a common sight in Zurich).

"These four factors, all derived from bus/tram networks and the road system, are astonishingly

accurate at explaining the differences in capacity that we see from city to city," explains Axhausen. These findings enabled them to firm up a theory that they had long been mulling over, drawn from earlier simulations and a small amount of empirical data: that, subject to the vehicular density in various cities, traffic volumes behave in a similar way and follow the same patterns.

"This means that we can use a city's infrastructure to predict the [critical point](#), and by extension, the traffic capacity of the network," explains Lukas Ambühl, a doctoral student in the Traffic Engineering group and one of the study's first authors.

### Calculating the ideal infrastructure

A layperson might think it rather obvious that a network's form is linked to its traffic capacity. However, the transport experts at ETH see it as anything but self-evident that a system as chaotic as an urban transport network, with thousands of participants all acting independently, really would follow the same patterns in all the cities examined. This is why they are particularly fascinated by this simple model.

The results are also of practical relevance: urban planners can now quantify their expectations of how planned investments or construction work will improve or limit their network's traffic capacity. For example, constructing (or removing) [road](#) lanes changes the density of the network, while a key bridge being rendered unusable due to renovation work diminishes its redundancy. And if [transport companies](#) arrange for public transport to run more frequently, there will be more buses on the roads.

However, the authors also note the limitations of the study. They explain that the sample, covering 41 cities, was small, and that most of these cities were in Europe. In addition, they did not undertake a detailed exploration of how traffic lights were controlled at intersections. Finally, the study only focused on infrastructure, disregarding questions of demand, such as how commuters react to a changed traffic situation.

Despite this, the results could help cities create

their ideal infrastructure. "Our new understanding of traffic [capacity](#) within urban networks may not do away with [traffic](#) jams for good. However, it will likely play a key role in improving the transport situation," Axhausen explains.

**More information:** Allister Loder et al. Understanding traffic capacity of urban networks, *Scientific Reports* (2019). [DOI: 10.1038/s41598-019-51539-5](#)

Provided by ETH Zurich

APA citation: How the road network determines traffic capacity (2019, November 19) retrieved 23 April 2021 from <https://techxplore.com/news/2019-11-road-network-traffic-capacity.html>

*This document is subject to copyright. Apart from any fair dealing for the purpose of private study or research, no part may be reproduced without the written permission. The content is provided for information purposes only.*